


Electric Chain Hoist



- ⚡ Capacities from 500kg to 5000kg.
- ⚡ Most tensile safety hooks without break.
- ⚡ Compact and high efficient motor with heat protection device.
- ⚡ Push button is with 24v low voltage to guarantee safety.
- ⚡ Limit switch.
- ⚡ Limit load device are fitted.
- ⚡ Both single phase and three phase are available.
- ⚡ IP54 protection on electric hoist for dust and water proof protection.



DC Brake




Limit Switches



Overload Clutch

Single Speed Type Single Phase Electric Chain Hoist


Item Number	Rated load (ton)	Lift (m)	Lifting speed (m/min)	Hoist Motor Output(kw)	1-phase Ins class	% ED	Lood chain Dia mm	Number of falls	Test load ton	Min Headroom Max	Net Weight (kg)
205	0.5	3	5.2	0.8	F	40	7.1	1	0.625	545	64
210	1	3	5.2	1.6	F	40	7.1	1	1.25	580	65
220	2	3	2.6	1.6	F	40	7.1	2	2.5	740	72
230	3	3	1.7	1.6	F	40	7.1	3	3.75	790	80



0.5T,1T

Single Speed Type Three Phase Electric Chain Hoist


Item Number	Rated load (ton)	Lift (m)	Lifting speed (m/min)	Hoist Motor Output(kw)	3-phase Ins class	% ED	Lood chain Dia mm	Number of falls	Test load ton	Min Headroom Max G(mm)	Net Weight (kg)
305	0.5	3	6.3	0.8	F	40	7.1	1	0.625	545	64
310	1	3	6.3	1.6	F	40	7.1	1	1.25	580	65
320	2	3	3.2	1.6	F	40	7.1	2	2.5	740	72
330	3	3	2.1	1.6	F	40	7.1	3	3.75	790	80
350	5	3	1.3	1.6	F	40	7.1	5	6.25	950	135



2T

Double Speed Type Three Phase Electric Chain Hoist


Item Number	Rated load (ton)	Lift (m)	Lifting speed (m/min)	Hoist Motor Output(kw)	3-phase Ins class	% ED	Lood chain Dia mm	Number of falls	Test load ton	Min Headroom Max G(mm)	Net Weight (kg)
305B	0.5	3	6.3/2.1	0.8/0.25	F	40	7.1	1	0.625	545	64
310B	1	3	6.3/2.1	1.2/0.4	F	40	7.1	1	1.25	580	65
320B	2	3	3.2/1	1.2/0.4	F	40	7.1	2	2.5	740	72
330B	3	3	2.1/0.7	1.2/0.4	F	40	7.1	3	3.75	790	80
350B	5	3	1.3/0.4	1.2/0.4	F	40	7.1	5	6.25	950	135



3T

Electric Chain Hoist Parameter

load (ton)	Lift	A	B	C	D	E	F	H
0.5	3	249	249	168	146	25	565	195
1	3	249	249	168	146	30	614	195
2	3	249	249	180	134	33	665	235
3	3	249	249	100	214	41	720	270



5T