

"FOR GUARANTEED TROUBLE FREE SERVICE"



SANT & SBM

V A L V E S

GUN METAL,
BRONZE,
CAST IRON &
STEEL VALVES

RETAIL PRICE LIST

List No. : SANT/RPL/ 01-2020

Dated : 15-01-2020

THIS CANCELS ALL OUR PREVIOUS PRICE LISTS.

GOODS & SERVICES TAX (GST @ 18%) EXTRA



For your kind attention

Dear Customer,

As usual; being always receptive to our valuable customer's feed back, we have added the following items in this price list, to meet your demands :-

1) SANT VALVES PVT. LTD.

NEW ADDED ITEMS			
Page No.	Item No.	Description	Remarks
26	IC-3	I.C. STAINLESS STEEL STEAM TRAP	NEW ITEM
30	CR-23	CAST IRON BUTTERFLY VALVE (LEVER OPERATED) MI SEAT	NEW ITEM
30	CR-24	CAST IRON BUTTERFLY VALVE (LEVER OPERATED) S.S. SEAT	NEW ITEM
32	CS-3A	CAST IRON 'Y' TYPE STRAINER	SIZE ADDED
51	RSV	DUCTILE IRON RESILIENT SEATED GATE/SLUICE VALVE	NEW ITEM

2) SANT WATERTECH PRIVATE LTD.

NEW ITEMS			
Page No.	Item No.	Description	Remarks
53	WM-7	ELECTROMAGNETIC FLOW METER	SIZE ADDED

3) SANT AUTOMATIONS & NEW TECH

NEW ITEMS			
Page No.	Item No.	Description	Remarks
54	SSBVF	STAINLESS STEEL BALL VALVE (F) SS-304	SIZE ADDED
55	CIBFE	CAST IRON BUTTERFLY VALVE WITH ELECTRIC ACTUATOR	SIZE ADDED
57	BFX	CAST IRON BUTTERFLY, REPLACEABLE SEAT & DISC	NEW ITEM

With warm regards

Rajesh Rathour
Director (Mktg. & Sales)



Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in bonnet inside screw rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Screwed female BSP Taper Threads to BS 21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/4	8	2304
3/8	10	2304
1/2	15	2387
3/4	20	2902
1	25	4254
1¼	32	6378
1½	40	8659
2	50	12596

IBR 1A

HSN CODE : 84818030



Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in bonnet inside screw rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanged as per BS 10 Table-H F.F. (undrilled)**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	5003
3/4	20	5754
1	25	7694
1¼	32	11633
1½	40	12541
2	50	18244

IBR 1B

HSN CODE : 84818030



Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in bonnet inside screw rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanges as per BS 10 Table F (undrilled)**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig.(10.54kg/cm²) at 435°F(225°C)**

1/2	15	4589
3/4	20	5446
1	25	7492
1¼	32	11404
1½	40	12285
2	50	17984

IBR 1C

HSN CODE : 84818030



Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted bonnet O/S & Yoke type rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Screwed female BSP Taper Threads to BS 21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

3/8	10	3421
1/2	15	3445
3/4	20	4767
1	25	7309
1¼	32	14362
1½	40	21199
2	50	25810
2½	65	42352
3	80	50693

IBR 2A

HSN CODE : 84818030




Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Bonnet outside screw & Yoke type rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanged as per BS 10 Table-H F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	8454
3/4	20	9697
1	25	13166
1¼	32	20117
1½	40	28248
2	50	40948
2½	65	50280
3	80	67902
4	100	94337

IBR 2B

HSN CODE : 84818030



Product : **Sant Bronze Globe Steam Stop Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Bonnet Outside screw & Yoke type rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanged as per BS 10 Table-F F.F. undrilled**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig.(10.55kg/cm²) at 435°F(225°C)**

1/2	15	8087
3/4	20	10005
1	25	12961
1¼	32	20629
1½	40	27890
2	50	40429
2½	65	43387
3	80	66866
4	100	93296

IBR 2C

HSN CODE : 84818030



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 End Details : **Screwed female BSP Taper Threads to BS 21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	2201
3/4	20	2750
1	25	3915
1¼	32	6063
1½	40	8290
2	50	11668

IBR 3A

HSN CODE : 84813000



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Screwed female BSP Taper Threads to BS 21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1½	40	17424
2	50	19618
2½	65	35559
3	80	48723

IBR 3B

HSN CODE : 84813000



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Flanges as per BS-10 Table-H F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm²)**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	4564
3/4	20	5183
1	25	6638
1¼	32	10364
1½	40	11921
2	50	16591

IBR 3C

HSN CODE : 84813000



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Flanges as per BS-10 Table-H F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm²) (Hyd.)**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

2½	65	47065
3	80	55672
4	100	75678

IBR 3D

HSN CODE : 84813000



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Flanges as per BS-10 Table-F F.F. undrilled**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm²) (Hyd.)**
 Working Pressure : **Max. BOP 150Psig.(10.54kg/cm²) at 435°F(225°C)**

2½	65	44577
3	80	52870
4	100	71534

IBR 3E

HSN CODE : 84813000



Product : **Sant Bronze Horizontal Lift Check Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Flanges as per BS-10 Table-F F.F. undrilled**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm²) (Hyd.)**
 Working Pressure : **Max. BOP 150Psig.(10.54kg/cm²) at 435°F(225°C)**

1/2	15	4147
3/4	20	4929
1	25	6480
1¼	32	10110
1½	40	11717
2	50	16334

IBR 3F

HSN CODE : 84813000



Product : **Sant Bronze Vertical Non Return Valve**
 Type of Pattern : **Vertical Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Two piece design**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Screwed female BSP Taper threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	2772
3/4	20	3400
1	25	4767
1¼	32	5858
1½	40	6533
2	50	9534

IBR 4A

HSN CODE : 84813000



Product : **Sant Bronze Vertical Non Return Valve**
 Type of Pattern : **Vertical Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Two piece design**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 End Details : **Flanges as per BS-10 Table-H F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	6063
3/4	20	7416
1	25	8502
1¼	32	10781
1½	40	13530
2	50	20271

IBR 4B

HSN CODE : 84813000



Product : **Sant Bronze Safety Valve**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Pop type open discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu alloy**
 End Details : **Inlet screwed male BSP Taper threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**
***Note : Please advice set pressure while placing order**

1/2	15	5754
3/4	20	10474
1	25	10574
1½	40	23116
2	50	40070

IBR 5

HSN CODE : 84814000



Product : **Sant Bronze Safety Valve**
 Type of Pattern : **Right Angle Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Pop type enclosed discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu alloy**
 End Details : **Inlet screwed male BSP Taper threads to BS-21**
Outlet screw female BSP Parallel threads to BS-21
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**
***Note : Please advice set pressure while placing order**

1/2	15	6042
3/4	20	10997
1	25	11102
1½	40	24272
2	50	42072

IBR 6

HSN CODE : 84814000



Product : **Sant Bronze Combined Feed Check Valve**
 Type of Pattern : **Right Angle Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Bolted Gland Flange & Screwed in cover**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu-Alloy**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanges as per BS 10 Table-H F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	7519
3/4	20	8099
1	25	11611
1¼	32	18659
1½	40	23116
2	50	42660

IBR 7

HSN CODE : 84813000



Product : **Sant Bronze Pressure Gauge Valve**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Type of Seat : **Plug Type**
 End Details : **Screwed female BSP Parallel threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

3/8	10	3215
1/2	15	3215

IBR 8

HSN CODE : 84812000



Product : **Sant Bronze Controllable feed check valve**
 Type of Pattern : **Straight type / Right Angle**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in bonnet O/s Yoke type rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI 410 Stainless Steel**
 Gland Packing : **Graphited Asbestos**
 End Details : **Screwed female BSP Taper Threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

3/8	10	2772
1/2	15	2772
3/4	20	4385
1	25	6378
1¼	32	15865
1½	40	23070
2	50	26330

IBR 9A

HSN CODE : 84813000



Product : **Sant Bronze Controllable feed check valve**
 Type of Pattern : **Right Angle / Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Screwed in bonnet O/s Yoke type rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI 410 Stainless Steel**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanges as per BS 10 Table-H FF undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	8573
3/4	20	9852
1	25	13992
1¼	32	17890
1½	40	26952
2	50	38658

IBR 9B

HSN CODE : 84813000



Product : **Sant Bronze Asbestos Packed Water Level Gauge**
 Type of Pattern : **Standard Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Right Hand Type/Left Hand Type**
 Gland Packing : **Lubricated Asbestos**
 End Details : **Screwed Male BSP Parallel threads to BS-21**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig.(10.54kg/cm²) at 435°F(225°C)**

Size/Inch mm Price / Pc.

3/8	10	7348
1/2	15	7348
5/8	16	9459
3/4	20	9459

IBR 10A

HSN CODE : 90261020



Product : **Sant Bronze Asbestos Packed Water Level Gauge**
 Type of Pattern : **Standard Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Right Hand Type/Left Hand Type**
 Gland Packing : **Lubricated Asbestos**
 End Details : **Flanges as per BS 10 Table-F FF undrilled**
 Test Pressure : **Tested to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig.(10.54kg/cm²(Hyd.)) at 435°F(225°C)**

3/8	10	10130
1/2	15	10130
5/8	16	12384
3/4	20	12384

IBR 10B

HSN CODE : 90261020



Product : **Sant Bronze Sleeve packed Water Level Gauge**
 Type of Pattern : **Standard Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **With automatic shut off device in water**
 Arm Right Hand Type/ Left Hand Type
 End Details : **Flanges as per BS-10 Table-H FF undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	15362
5/8	16	19342
3/4	20	19342

IBR 11A

HSN CODE : 90261020



Product : **Sant Bronze Sleeve packed Water Level Gauge**
 Type of Pattern : **Standard Pattern**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **With automatic shut off device in water**
 Arm Right Hand Type/ Left Hand Type
 End Details : **Screwed Male BSP Parallel threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1/2	15	13244
5/8	16	18096
3/4	20	18096

IBR 11B

HSN CODE : 90261020

Product : **Sant Bronze Sleeve packed Water Level Gauge (Spare Drain)**

Size/Inch	mm	Price / Pc.
1/2	15	2201
3/4	20	2201

IBR 11C

HSN CODE : 90261020



Product : **Sant Bronze Y Type Strainer**
 Type of Pattern : **Y Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Y Type Screwed in cover**
Brass/SS304 Screen having 0.5mm Dia perforations
 End Details : **Screwed Male BSP Taper Thread to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² Hyd.)**
 Working Pressure : **Max. BOP 250Psig.(17.58 kg/cm²) at 435°F(225°C)**

1/2	15	1040
3/4	20	1712
1	25	3528
1¼	32	4460
1½	40	6427
2	50	12025

IBR 12A

HSN CODE : 84818030



Product : **Sant Bronze Y Type Strainer**
 Type of Pattern : **Y Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Y Type Screwed in cover**
Brass/SS304 Screen having 0.5mm Dia perforations
 End Details : **Flanges as per BS-10 Table H, FF undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² Hyd.)**
 Working Pressure : **Max. BOP 250Psig.(17.58 kg/cm²) at 435°F(225°C)**

1/2	15	3736
3/4	20	5337
1	25	8037
1¼	32	10731
1½	40	16533
2	50	24775

IBR 12B

HSN CODE : 84818030



Product : **Sant Bronze Fusible Plug**
 Type of Pattern : **Two piece design**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Two piece design**
 End Details : **Screwed male BSP Taper thread to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² Hyd.)**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**
***Note : Melting temperature of Fusible Alloy 270°C**

1/2	15	1712
3/4	20	1732
1	25	1987
1¼	32	2512
1½	40	2902
2	50	4254

IBR 13

HSN CODE : 84814000

(a)

SPARE CONES FOR THE FUSIBLE PLUG

1/2	15	934
3/4	20	934
1	25	1140
1¼	32	1556
1½	40	1556
2	50	2178

IBR 13A

HSN CODE : 84814000



Product : **Sant Bronze Fusible Plug**
 Type of Pattern : **One piece design**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **One piece design**
 End Details : **Screwed male BSP Taper threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**
***Note : Melting temperature of Fusible Alloy 270°C**

Size/Inch	mm	Price / Pc.
1/2	15	1061
3/4	20	1061
1	25	1732

IBR 14

HSN CODE : 84814000



Product : **Sant Bronze Sight Glass**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **With toughend glass window upto and including 25mm size and double window for size above 25mm**
 End Details : **Screwed female BSP Taper Threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	1922
3/4	20	2512
1	25	2714
1¼	32	5133
1½	40	5337
2	50	6273

IBR 15

HSN CODE : 84818030



Product : **Sant Bronze Parallel Slide Blow off Valve**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Rack & Pinion Operated with Key**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS 410/Monel**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanges as per BS-10 Table H, F.F. undrilled**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1	25	24775
1¼	32	31052
1½	40	35762
2	50	52511
2½	65	81847
3	80	93472

IBR 16

HSN CODE : 84818030



Product : **Sant Bronze Pressure Reducing Valve**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Spring Loaded outlet pressure range available 5/60, 20/80, 40/125 Psig**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **SS 304 Diaphragm**
 End Details : **Screwed female BSP Taper threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

Size/Inch	mm	Price / Pc.
1/2	15	8871
3/4	20	12493
1	25	17890
1¼	32	24101
1½	40	29025
2	50	43803

IBR 17

HSN CODE : 84811000



Product : **Sant Bronze Relief Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **GM IS 318 LTB2**
 Product Description : **Spring Loaded open discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu-Alloy**
 End Details : **Screwed male BSP Taper threads to BS-21**
 Test Pressure : **Shell test pressure to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Set pressure 10.54 kg/cm²g. (Suitable for Water & Air)**
***Note : Please advise set pressure while placing order**

Size/Inch	mm	Price / Pc.
1/4	8	1845
3/8	10	1845
1/2	15	1892
3/4	20	2543
1	25	3577
1¼	32	5288
1½	40	5995
2	50	9831

IBR 21

(WITH WORKS CERTIFICATE ONLY)

HSN CODE : 84814000



Product : **Sant Bronze Relief Valve**
 Type of Pattern : **Right Angle**
 Body Material cum standard : **GM IS 318 LTB2**
 Product Description : **Spring Loaded enclosed discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu-Alloy**
 End Details : **Inlet end male BSP Parallel threads outlet female BSP Parallel thread to BS-21**
 Test Pressure : **Shell test pressure to 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Set pressure 10.54 kg/cm²g. (Suitable for Water & Air)**
***Note : Please advise set pressure while placing order**

1/4	8	2025
3/8	10	2025
1/2	15	2071
3/4	20	2802
1	25	3789
1¼	32	5404
1½	40	7479
2	50	11814

IBR 22

(WITH WORKS CERTIFICATE ONLY)

HSN CODE : 84814000



Product : **Sant Bronze Pilot Operated R Type Reducing Valve**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Pilot operated R-type outlet pressure range available 5/60, 20/80, 40/125 Psig.**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI 410/Monel**
 End Details : **Flanges as per BS: 10 Table-H FF undrilled**
 Test Pressure : **Shell Test Pressure 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) steam Max Temp.(225°C)**
***Note : Please advise outlet pressure while placing order.**

1	25	41364
1¼	32	52561
1½	40	55830
2	50	77440

IBR 23

HSN CODE : 84811000



Product : **Sant Bronze Safety Valve**
 Type of Pattern : **Right Angle**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Spring Loaded Enclosed Discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable Disc**
 Trim : **Cu-Alloy**
 End Details : **Inlet end male BSP Taper thread outlet female BSP threads to BS-21**
 Test Pressure : **Shell test pressure 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig. at 435°F(225°C) Steam**
***Note : Please advise set pressure while placing Order.**

1/2	15	4024
3/4	20	5767
1	25	8059
1½	40	12842
2	50	19158

IBR 24

HSN CODE : 84814000



Product : **Sant Bronze Safety Valve**
 Type of Pattern : **Straight Type**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Spring Loaded Open Discharge**
 Type of Seat : **Integral**
 Type of Disc : **Renewable**
 Trim : **Cu-Alloy**
 End Details : **Inlet threads BSPT Taper**
 Test Pressure : **Shell test pressure 300Psig. Hyd. (21.09 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 150Psig. at 435°F(225°C) Steam**
***Note : Please advise set pressure while placing Order.**

Size/Inch	mm	Price / Pc.
1/2	15	3832
3/4	20	5491
1	25	7676
1½	40	12230
2	50	18244

IBR 25

HSN CODE : 84814000



Product : **Sant Bronze Mobrey Valve**
 Type of Pattern : **Right Angle**
 Body Material cum standard : **Bronze (IBR Clause 282(a) IV Gr. B**
 Product Description : **Screwed in bonnet inside screw rising stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **AISI-410 Stainless Steel**
 Gland Packing : **Graphited Asbestos**
 End Details : **Flanges as per BS-10 Table H (F.F. undrilled)**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² Hyd.)**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) at 435°F(225°C)**

1	25	19954

IBR 26

HSN CODE : 84818030



Product : **Sant Bronze Loco Type Fusible Plug**
 Body Material cum standard : **Bronze IBR Clause 282 (a) IV GrB**
 Product Description : **Loco Type two piece design**
 End Details : **Male BSP Taper Threads to BS-21**
 Test Pressure : **Tested to 500Psig. Hyd. (35.15 kg/cm² (Hyd.))**
 Working Pressure : **Max. BOP 250Psig.(17.58kg/cm²) Steam at 435°F(225°C)**

1	25	3062
1¼	32	3268

IBR 27

HSN CODE : 84814000

TERMS & CONDITIONS

1. Your Orders/Indents will be supplied on rates prevailing at the time of dispatch.
2. All orders placed direct or through Agent are valid only after confirmation from Head Office.
3. Rates are Ex-works, Jalandhar and inclusive of packing charges.
4. Every precaution is being taken while packing the goods which are generally booked at Railway/
5. Transport Risk but in case of any damage, loss or pilferage in transit we are not liable to accept any responsibility. Carriers would be considered as Indentor's Agent after a consignment is handed over by us to the former. Any Claim due to losses in transit or wrong delivery shall be concern between indentor and his carriers.
6. Order once placed and confirmed by us cannot be cancelled without our consent. We reserve the right to execute any order in full or in parts according to our supply position or manufacturing capacity. We accept no liabilities for delayed supplies for reasons beyond our control such as war, lockout breakdown or riots, etc. All commitments entered into by us are subject to above contingencies beyond our control.
7. Each consignment despatched contains Packing Slip. Any Shortage found in package received intact, should be reported to us for verification with in 7 DAYS from the date of taking delivery. Unless otherwise agreed upon all Way Bills or Railway Receipts for goods supplied shall be negotiated through scheduled Bank against payment only or per V.P.P.
New customers are requested to remit 25% of the value of the order as advance.
8. **Goods & Services Tax (GST@18%) will be charged extra as applicable.**
9. All disputes arising out of an order placed direct or through an Agent will be Subject to Jurisdiction of Law Courts at Jalandhar.
10. Rates & Terms are subject to alteration without notice.

-: NOTE :-

**ALL FLANGED VALVES ARE SUPPLIED UNDRILLED
UNLESS SPECIFIED BY THE INDENTOR**