



# ECO Lighting Supplies

**Address:** P.O. Box 337, Moonah. TAS. Australia 7009 **Email:** [admin@ecolightingsupplies.com.au](mailto:admin@ecolightingsupplies.com.au)  
**Website:** [www.ecolightingsupplies.com.au](http://www.ecolightingsupplies.com.au) **Phone:** 1300 ALL LED

# Our Story

At ECO Lighting Supplies we aim to offer Australia's leading edge lighting products. Utilising cutting edge technology to ensure our products are unmatched in the industry for energy efficiency without compromising quality of build and light delivery.

Each light is made to full SAA certification and is made with the highest quality material. This is also backed up with a full 5 year replacement warranty on 100% of our product range.

Help the environment. Reduce your carbon footprint and start saving money today.





## ECO-T1000610KCR (10w)

Size: 600\*26mm

Input Voltage: 100-240V 50/60Hz

LED Qty: 72pcs

Colour Temperature: 3000k-3500k, 4000k-4500k, 5000k-5500k, 6000k-6500k

Luminous Flux: 900-1100lm

CRI: >80

THD <15

Beam Angle: 120°- 160°

Cover: Clear Striped Milky



## ECO-T1001218KCR (18w)

Size: 1200\*26mm

Input Voltage: 100-240V 50/60Hz

LED Qty: 120pcs

Colour Temperature: 3000k-3500k, 4000k-4500k, 5000k-5500k, 6000k-6500k

Luminous Flux: 1800-2000lm

CRI: >80

THD <15

Beam Angle: 120°- 160°

Cover: Clear Striped Milky



## ECO-T1001225KCR (25w)

Size: 1200\*26mm

Input Voltage: 100-240V 50/60Hz

LED Qty: 120pcs

Colour Temperature: 3000k-3500k, 4000k-4500k, 5000k-5500k, 6000k-6500k

Luminous Flux: 2500-2700lm

CRI: >80

THD <15

Beam Angle: 120°- 160°

Cover: Clear Striped Milky



## ECO-T1001522KCR (22w)

Size: 1500\*26mm

Input Voltage: 100-240V 50/60Hz

LED Qty: 168pcs

Colour Temperature: 3000k-3500k, 4000k-4500k, 5000k-5500k, 6000k-6500k

Luminous Flux: 2200-2400lm

CRI: >80

THD <15

Beam Angle: 120°- 160°

Cover: Clear Striped Milky



## ECO-T1001532KCR (32w)

Size: 1500\*26mm

Input Voltage: 100-240V 50/60Hz

LED Qty: 216pcs

Colour Temperature: 3000k-3500k, 4000k-4500k, 5000k-5500k, 6000k-6500k

Luminous Flux: 3200-3500lm

CRI: >80

THD <15

Beam Angle: 120°- 160°

Cover: Clear Striped Milky



## Why choose ECO-T100 led tube?

- ☆ Up to 110lm/w
- ☆ PF>0.96, THD<15, Flicker free by Camera
- ☆ Isolated driver with Rubycon capacitor, 50000 hours lifetime
- ☆ Aluminum PCB+100% aluminum tube housing, Excellent heat sink
- ☆ CE, SAA C-TICK, RoHS certificate
- ☆ Warranty: 5 years. Locking rotatable end caps



# ECO Lighting Supplies

**Address:** P.O. Box 337, Moonah. TAS. Australia 7009 **Email:** [admin@ecolightingsupplies.com.au](mailto:admin@ecolightingsupplies.com.au)  
**Website:** [www.ecolightingsupplies.com.au](http://www.ecolightingsupplies.com.au) **Phone:** 1300 ALL LED