



ECO Lighting Supplies

Address: P.O. Box 337, Moonah, TAS. Australia 7009 **Email:** admin@ecolightingsupplies.com.au
Website: www.ecolightingsupplies.com.au **Phone:** 1300 ALL LED

Our Story

At ECO Lighting Supplies we aim to offer Australia's leading edge lighting products. Utilising cutting edge technology to ensure our products are unmatched in the industry for energy efficiency without compromising quality of build and light delivery.

Each light is made to full SAA certification and is made with the highest quality material. This is also backed up with a full 5 year replacement warranty on 100% of our product range.

Help the environment. Reduce your carbon footprint and start saving money today.





ECO-T05W102-3 (10w)

1. Light source: 1*10W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 1350lm
4. CE-EMC Constant Current Driver
5. Input Voltage: 100-240VAC
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 133*180*57mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T01W202-3 (20w)

1. Light source: 1*10W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 2700lm
4. CE-EMC Constant Current Driver
5. Input Voltage: 100-240VAC
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 133*180*57mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T02W302-3 (30w)

1. Light source: 1*30W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 4050lm
4. Input Voltage: 100-240VAC
5. CE-EMC Constant Current Driver
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 178*215*81mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T04W502-3 (50w)

1. Light source: 1*50W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 6750lm
4. Input Voltage: 100-240VAC
5. CE-EMC Constant Current Driver
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 194*253*95mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug




ECO-T06W702-3 (70w)

1. Light source: 1*70W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 9450lm
4. Input Voltage: 100-240VAC
5. CE-EMC Constant Current Driver
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 250*291*116mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug




ECO-T07W1002-31 (100w)

1. Light source: 1*100W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 13500lm
4. Input Voltage: 100-240VAC
5. State of the art **Meanwell Driver**
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 250*340*116mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T08W1202-31 (120w)

1. Light source: 2*60W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 16200lm
4. Input Voltage: 100-240VAC
5. State of the art **Meanwell Driver**
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 310*375*187mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T08W1502-3 (150w)

1. Light source: 2*70W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 20250lm
4. Input Voltage: 100-240VAC
5. State of the art **Meanwell Driver**
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 310*375*187mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T09W1802-31 (180w)

1. Light source: 4*45W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 24300lm
4. Input Voltage: 100-240VAC
5. State of the art **Meanwell Driver**
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 340*400*192mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO-T09W2002-31 (200w)

1. Light source: 4*50W COB LED
2. LED Chip: Bridgelux
3. Led Lumen: 27000lm
4. Input Voltage: 100-240VAC
5. State of the art **Meanwell Driver**
6. CCT: 2500-8000K
7. Beam Angle: 120°
8. Dimension: 340*400*192mm(L*W*H)
9. IP65 Rated
10. Housing: black, die-casting, aluminium, Toughened Glass
11. Cable: 0.75m VDE without plug



ECO Lighting Supplies

Address: P.O. Box 337, Moonah, TAS. Australia 7009 **Email:** admin@ecolightingsupplies.com.au
Website: www.ecolightingsupplies.com.au **Phone:** 1300 ALL LED