



ECO Lighting Supplies

Address: P.O. Box 337, Moonah. TAS. Australia 7009 **Email:** admin@ecolightingsupplies.com.au

Website: www.ecolightingsupplies.com.au **Phone:** 1300 ALL LED

Our Story

At ECO Lighting Supplies we aim to offer Australia's leading edge lighting products. Utilising cutting edge technology to ensure our products are unmatched in the industry for energy efficiency without compromising quality of build and light delivery.

Each light is made to full SAA certification and is made with the highest quality material. This is also backed up with a full 5 year replacement warranty on 100% of our product range.

Help the environment. Reduce your carbon footprint and start saving money today.





PHILIPS
LUMILEDS

ECO-400W-HM

Electrical Specifications:

Input Voltage: VAC90-305V

LED Power: 400W

Operating Humidity: 10%-90%

Operating Temperature: -40°C - 50°C

Power Factor (PF): > 0.95

Power Supply Efficiency: > 90%

Driver: Meanwell

Light Source: Phillips Luxeon

Mechanical Specifications:

IP Rating: IP 67

Warranty: 5 Year Warranty

Heat Radiator: Anodized Aluminium

Fixture Dimensions: 340*486*404mm

Net Weight: 16kg

Photometric Specifications:

Initial Luminous Flux: 38,000lm

Maintain Luminous Flux: 34,000lm

Color Rendering Index (CRI): Ra > 80



Color Temperature: 3,000-3,500K,
4,000-4,500K, 5,000-6,500K

Packing Information:

Packing Type: 1 Unit / Carton

Packing Dimension: 526*390*326mm

Packing Weight: 16.9kg





PHILIPS
LUMILEDS

ECO-550W-HM

Electrical Specifications:

Input Voltage: VAC90-305V

LED Power: 550W

Operating Humidity: 10%-90%

Operating Temperature: -40°C - 50°C

Power Factor (PF): > 0.95

Power Supply Efficiency: > 90%

Driver: Meanwell

Light Source: Phillips Luxeon

Mechanical Specifications:

IP Rating: IP 67

Warranty: 5 Year Warranty

Heat Radiator: Anodized Aluminium

Fixture Dimensions: 340*486*404mm

Net Weight: 16kg

Photometric Specifications:

Initial Luminous Flux: 49,500lm

Maintain Luminous Flux: 49,000lm

Color Rendering Index (CRI): Ra > 80



Color Temperature: 4,000K

Packing Information:

Packing Type: 1 unit / carton

Packing Dimension: 526*390*326mm

Packing Weight: 16.9kg





ECO Lighting Supplies

Address: P.O. Box 337, Moonah. TAS. Australia 7009 **Email:** admin@ecolightingsupplies.com.au

Website: www.ecolightingsupplies.com.au **Phone:** 1300 ALL LED