

**Welcome to Concord Lifting Equipment Ltd. We are one company with four locations.**

All our engineers are extensively trained in courses with our manufacturers to provide the very best service for our customers who come back to us time and time again. Remember we don't just hire, we also sell, repair, maintain and test all material handling and height equipment anywhere in the world and have been doing so successfully for years.

## Contents

<b>Lifting</b>	Electric Chain Hoists	2
	Gantry Hoist & Wire Rope Hoist	3
	Minifor Winch & Tirak Winch	4
	Gin Wheel & Rope	4
	Manual Chain Block	5
	Ratchet Lever Hoist	5
	Manual Tirfor Winch	6
	Adjustable mobile gantries	6
	Spreader Beams / Niko Track	7
	Genie Machines	8
	Plasterboard Lifter	9
	Floor Crane	9
Adjustable Height Hoist Support	9	
Jacks	10	
Manhole Lifter	11	
<b>Lifting Accessories</b>	Girder Trolley & Plate Clamp	12
	Adjustable Girder Clamp	12
	Transformer and leads	13
	Flat Belt Sling/Round Sling	13
	Chain Slings- 1 leg, 2 leg, 4 leg	14
	Barrow Sling & Skip Lifting assembly	15
	Dee & Bow Shackles	15
	Manhole ring lifting pin	16
	Buckets/Muck Skips	16
	Frimda/Deha clutches	16
<b>Moving</b>	Brick Lift/Crane Forks	17
	Block Grabs & Bottle Carrier	17
	Kerb Handling / Vacuum Block Grab	18
	Fork Truck Tine bracket / Jib Booms	18
	Man Riding cages/Stretcher cage	19
	Pipe or Beam bogie	19
	Pallet Truck/Rough Terrain pallet truck	20
	Flat Top/Turnable Truck/Sack Truck	21
	Stair Climber / Plaster Board Trolley	21
	Piano Skate / Skoots	22
	Furniture Moving Trolley/Skate	22
	Roller Crowbar / Machine Skates	23
<b>Safety</b>	Safety harness & Inertia Reel	24
	Temporary lifeline / Roof Man Anchor	24
	Man Riding Tripod / Bosun's chair	25
<b>Vacuum Handling</b>	Vacuum handlers	26
	Stillage Trolley	26
<b>Test Weights</b>	Test Weights	27
	Load Cells / Load Indicators	27
<b>Concord Information</b>	Terms & Conditions	28
	Where to find us, Guidelines	31





- Take the hard work out of lifting and lowering loads through vertical distances.
- Runs off 110v, 1ph supply
- Lift heights from 6M to 36M
- 250kgs to 3T

110-Volt Electric Chain Hoist Technical Specification					
H.O.L (M)	250kgs	500kgs	1T	2T	3T
6 M	8m/min	4m/min	4m/min	2m/min	1.35m/min
9 M	8m/min	4m/min	4m/min	2m/min	1.35m/min
12 M	8m/min	4m/min	4m/min	2m/min	1.35m/min
15 M	8m/min	4m/min	4m/min	2m/min	N/A
18 M	8m/min	4m/min	4m/min	2m/min	N/A
24 M	8m/min	4m/min	4m/min	N/A	N/A
30 M	8m/min	4m/min	4m/min	N/A	N/A
36 M	8m/min	4m/min	4m/min	N/A	N/A



- Take the hard work out of lifting and lowering loads through vertical distances
- Runs off 400/440v, 3ph supply
- Lift heights from 6M to 30M
- Dual speed an option on power travel trolley
- 500kgs to 5T
- Travel trolley has power speed of 12M/min

440-Volt 3ph Electric Chain Hoist Technical Specification					
H.O.L (M)	500kgs	1T	2T	3T	5T
6 M	9M/min	8M/min	4M/min	2.9M/min	2.9M/min
9 M	9M/min	8M/min	4M/min	2.9M/min	2.9M/min
12 M	9M/min	8M/min	4M/min	2.9M/min	2.9M/min
15 M	9M/min	8M/min	4M/min	2.9M/min	2.9M/min
18 M	9M/min	8M/min	4M/min	2.9M/min	2.9M/min
24 M	9M/min	8M/min	4M/min	2.9M/min	N/A
30 M	9M/min	8M/min	4M/min	2.9M/min	N/A

Extra-Power travel trolley  
£ POA



- Easy to assemble
- Simple to operate
- Available in variety of sizes
- 110v, 1ph
- The Scaffold hoist can be swung in by one hand
- The Gantry hoist can be pulled in by one hand
- Both will accept a variety of slings or buckets to facilitate lifting loads

**300kgs Gantry Hoist**  
**150/200kgs Scaffold Hoist**  
**Technical Specification**

H.O.L (M)	S.W.L	Type
<b>30 M</b>	300 kgs	Beam Mounted Gantry Hoist
<b>30 M</b>	300 kgs	Frame mounted Gantry Hoist
<b>25 M</b>	150 kgs	Scaffold Hoist
<b>30 M</b>	200 kgs	Scaffold Hoist

On the frame mounted versions not tied back to a scaffold but standing independently on the roof, 14 No x 25kgs hand weights will be required at an additional rate of £1.50 per weight per week.

**230kgs Wire Rope Hoist**  
**Technical Specification**

- CWS 230
- Rapid lift wire rope hoist
- 14M/min

230 kgs x 24 M



- The Minifor and Tirak from Tractel are portable lightweight hoists
- Enables an unlimited height of lift



**300/500kgs 110v Minifor Winch  
1T 440v Tirak Winch  
Technical Specification**

Model	S.W.L
TR 30	300 kgs
TR 50	500 kgs
Tirak	1T
TR 50	Radio Controlled
TR 30	Radio Controlled

**Minifor/Tirak wire ropes to suit TR30,  
TR50 & Tirak**

Model	Length (Metres)
TR 30	20 M
TR 30	30 M
TR 30	40 M
TR 30	50 M
TR 30	60 M
TR 30	80 M
TR 50	30 M
TR 50	40 M
TR 50	50 M
TR 50	60 M
Tirak	30 M
Tirak	40 M
Tirak	50 M

**Manual pulley used with varying length ropes.  
250kgs Gin Wheel**

10M Rope
20M Rope
30M Rope
40M Rope



- Lightweight construction with heavy-duty capability
- All are available with slack chain bags for rigging applications
- Versatile and reliable

Manual Chain Block Technical Specification					
H.O.L (M)	S.W.L	S.W.L	S.W.L	S.W.L	S.W.L
<b>3 M</b>	500kg	1T	2T	3T	5T
<b>6 M</b>	500kg	1T	2T	3T	5T
<b>9 M</b>	500kg	1T	2T	3T	5T
<b>12 M</b>	500kg	1T	2T	3T	5T
<b>15 M</b>	500kg	1T	2T	N/A	N/A
<b>18 M</b>	500kg	1T	2T	N/A	N/A
<b>24 M</b>	500kg	1T	2T	N/A	N/A
<b>30 M</b>	500kg	1T	N/A	N/A	N/A
<b>Chain Bag</b>					



- For work in confined spaces
- Ideal for pulling or positioning loads
- Available in 750kg to 6T capacities with a standard 1.5M height of lift (longer if required)

Ratchet/Lever Hoist Technical Specification				
H.O.L (M)	S.W.L	S.W.L	S.W.L	S.W.L
<b>1.5 M</b>	750kgs	1.5T	3T	6T
<b>3 M</b>	750kgs	1.5T	3T	6T
<b>6 M</b>	750kgs	1.5T	3T	6T



- A compact winch for high lifts and long hauls
- Incorporating all the quality associated with the Tractel brand
- Tirfors are available in up to 3.2T lifting capacity
- Heavier loads can be handled when used in combination with Snatch Blocks
- All winches supplied with operating handle
- 60M & 100M ropes supplied on cable reel

**Manual Tirfor Winch  
Electric Hydraulic Tirfor Winch  
Technical Specification**

Model	Capacity
<b>TU8</b>	800 kgs
<b>TU16</b>	1.6 T
<b>TU32</b>	3.2 T

**Wire ropes to suit TU8, TU16 & TU32**

Rope Length (M)	TU8	TU16	TU32
<b>10 M</b>	POA	POA	POA
<b>20 M</b>	POA	POA	POA
<b>30 M</b>	POA	POA	POA
<b>40 M</b>	POA	POA	POA
<b>60 M</b>	POA	POA	POA
<b>100 M</b>	POA	POA	POA

**Electric 440v, Hydraulic power packs to suit  
TU16 or TU32 are available  
Price on application**

**Adjustable Mobile Gantries  
Technical Specification**

S.W.L	Height to U.S.B	Span (Metres)
<b>1 T</b>	1.8 – 3 M	3 M
<b>1 T</b>	1.8 – 3 M	4 M
<b>1 T</b>	2.5 – 4.5 M	3 M
<b>2 T</b>	1.8 – 3 M	3 M
<b>2 T</b>	1.8 – 3 M	4 M
<b>2 T</b>	2.5 – 4.5 M	3 M
<b>3 T</b>	1.8 – 3 M	3 M
<b>3 T</b>	1.8 – 3 M	4 M

- Capable of handling up to 3T
- Provides a portable lifting point
- Demountable for ease of transport

**SHEAR LEGS/TRIPOD**

- Portable lifting tripod
- Tackles below ground lifting and lowering tasks

S.W.L	Height (M)
<b>500kgs</b>	2 M – 3 M
<b>1 T</b>	2 M – 3 M



- Fixed, adjustable and modular lifting and spreader beams up to 15T capacity
- Allows big loads to be lifted safely from a single suspension point
- Concord supply for hire or sale

Spreader Beams Technical Specification	
S.W.L	Length (Metres)
9.5 T	1.5 M
15 T	2.5 M
9.5 T	3.6 M
9.5 T	4.2 M
9.5 T	9.6 M

**Other sizes available**



- Installation & testing is available at additional cost
- Supplied in 3M lengths
- Hire rate includes hanging brackets/Gravloks, joining plates & endstops

Lightweight Niko Track System Runway Beams Technical Specification					
Type	Niko 25	Niko 26	Niko 27	178 x 102 mm Beam	254 x 102 mm Beam
S.W.L	Up to 500 kgs	Up to 800 kgs	Up to 1T	Up to 1.5T	Up to 3T
Track/Beam per 3M	POA	POA	POA	POA	POA
4-Wheel Trolley to suit Niko Track	POA	POA	POA	Requires Girder Trolley	



- Compact models
- Allows lifting and manoeuvres in congested work areas with ease
- The Air Hoist includes one gas bottle, any additional bottles are a one-off charge

**Genie Machines  
Technical Specification**

Model No	S.W.L	Height of Lift (Metres)
<b>GL 10</b>	159 kgs	3.05 M
<b>GL 12</b>	159 kgs	3.66 M
<b>SLA 10</b>	454 kgs	3.05 M
<b>SLC 12</b>	295 kgs	3.66 M
<b>SLA 15</b>	363 kgs	4.57 M
<b>SLC 18</b>	295 kgs	5.48 M
<b>SLA 20</b>	363 kgs	6.1 M
<b>SLC 24</b>	295 kgs	7.32 M
<b>SLA 25</b>	295 kgs	7.62 M
<b>GH 3.8 Air Superhoist</b>	159 kgs	3.8 M
<b>GH 5.6 Air Superhoist</b>	136 kgs	5.6 M
<b>R250</b>	682 kgs	7.62 M
<b>Counter balance unit (SLA only) or ext. tee</b>		

**Additional gas bottle POA**

- Transforms your Superlift into a vertical crane or hoist.
- Positions tooling fixtures, hoists circuit breakers, engines etc.

**Genie Jib Booms**  
**Weekly Rate**  
POA

- Fits easily over standard or adjustable forks – no tools required to install or remove. Assists in loading and unloading heavy objects

**Genie Load Platforms**  
**Weekly Rate**  
POA







- The Scott-Jack plasterboard lifter is one or two person operation
- Lightweight system

### Plasterboard Lifter Technical Specification

1.8 – 3.1 M Lift



- Immensely successful in the automotive trade
- Equally useful in other environments are our hydraulic floor cranes
- Counter balance units for external lifting point

### Floor Crane Technical Specification

S.W.L	TYPE
800kgs	Fold away
1T	Fixed
500kgs	Counter balance
1T	Counter balance
500kgs	Counter balance-demountable
	Additional weights (500kgs) (1 T)

### Adjustable Height Hoist Support System Technical Specification

- Comprising of a pivot arm
- An adjustable height Yoke and weight tray
- Provides a counter balanced external support point

S.W.L
Max 300 kgs
Max 500 kgs



## HYDRAULIC RAMS

Also available

- Solid and Hollow
- Low height
- Double acting
- Locking collars
- Electric pumps

Stroke/ Capacity	50mm	100mm	150mm	250mm
<b>Up to 5 T</b>	P.O.A	P.O.A	P.O.A	P.O.A
<b>Up to 10 T</b>	P.O.A	P.O.A	P.O.A	P.O.A
<b>Up to 20 T</b>	P.O.A	P.O.A	P.O.A	P.O.A
<b>Up to 30 T</b>	P.O.A	P.O.A	N/A	N/A
<b>Up to 50 T</b>	P.O.A	P.O.A	P.O.A	P.O.A
<b>Up to 100 T</b>	P.O.A	P.O.A	P.O.A	P.O.A
<b>More than 100 T</b>	P.O.A	P.O.A	P.O.A	P.O.A

## HYDRAULIC PUMPS AND ACCESSORIES

- Detached hydraulic pump and ram sets
- 5 to 100 tonne capacity with a range of fittings and sizes to suit all tasks

Pump to suit single Ram	Pump to suit multiple Rams	Gauges	2-Way Manifold	4-Way Manifold
P.O.A	P.O.A	P.O.A	P.O.A	P.O.A

Complete with 2 metre Hose



## Manhole Lifter Technical Specification

- Lightweight
- Complete with keys
- Width/Length adjustable
- Easy assembly/dismantling

2 KEY

4 KEY





- Designed to carry electric or hand chain hoists on girders, RSJ's or beams
- Supplied in push travel or geared travel
- 500kg to 10T safe working load and from 60mm-305mm widths

### Girder Trolley Technical Specification

Capacity	Beam Size
1 T	50 – 220mm
2 T	66 – 220mm
3 T	74 – 220mm
5 T	90 – 220mm
10 T	136 – 305mm

### Plate Clamps Technical Specification

Capacity	Beam Size
1 T	0-20mm
1.5 T	0-20mm
2 T	0-25mm
6 T	0-50mm

- For lifting single sheets of metal vertically
- Requires minimum weight of 1/10 S.W.L

### Adjustable Girder Clamp Technical Specification

Capacity	Beam Size
1 T	75 – 235mm
2 T	70 – 245mm
3 T	100 – 300mm
3 T	70 – 355mm
5 T	70 – 355mm
5 T	200 – 457mm
10 T	80 – 350mm
<b>3 T Side – loading clamp</b>	125 - 204mm



- Static attachment for joining lifting equipment e.g. chain hoist or electric hoist to a girder or beam
- Easy to install clamps



For 110-VOLT Hoists

### Transformer/Leads Technical Specification

<b>3.0 kVA</b>	Twin 16amp
<b>5.0 kVA</b>	Single 32amp. Twin 16amp

The 3kVA and 5kVA are complete with 20m x 4mm extension lead (16 or 32amp)



- Choose flat slings for maximum load stability

Chain Slings next page!

### Flat Belt Webbing Slings Technical Specification

E.W.L	1T Violet	2T Green	3T Yellow	5T Red
<b>1 M</b>	POA	POA	POA	POA
<b>2 M</b>	POA	POA	POA	POA
<b>3 M</b>	POA	POA	POA	POA
<b>4 M</b>	POA	POA	POA	POA
<b>5 M</b>	POA	POA	POA	POA
<b>6 M</b>	POA	POA	POA	POA

### Round Slings Polyester

E.W.L	1T Violet	2T Green	3T Yellow	5T Red
<b>0.5 M</b>	POA	POA	POA	POA
<b>1 M</b>	POA	POA	POA	POA
<b>1.5 M</b>	POA	POA	POA	POA
<b>2 M</b>	POA	POA	POA	POA
<b>2.5 M</b>	POA	POA	POA	POA
<b>3 M</b>	POA	POA	POA	POA

- Gentle on the load
- Ideal choice for use in situations where chain slings could pose problems
- Use round slings for use on loads where extra grip is required

**Chain Slings  
Grade 80 Alloy Single Leg  
Technical Specification**

E.W.L	S.W.L 1.5T	S.W.L 3.15T	S.W.L 5.3T	S.W.L 8T
<b>1 M</b>	7mm	10mm	13mm	16mm
<b>2 M</b>	7mm	10mm	13mm	16mm
<b>3 M</b>	7mm	10mm	13mm	16mm
<b>4 M</b>	7mm	10mm	13mm	16mm
<b>6 M</b>	7mm	10mm	13mm	16mm

- Supplied with safety hooks and shortening clutches



- Supplied with safety hooks and shortening clutches

**Chain Slings  
Grade 80 Alloy Two Leg  
Technical Specification**

E.W.L	S.W.L 2.1T @ 0° - 45°	S.W.L 4.25T @ 0° - 45°	S.W.L 7.5T @ 0° - 45°	S.W.L 11.2T @ 0° - 45°
<b>2 M</b>	7mm	10mm	13mm	16mm
<b>3 M</b>	7mm	10mm	13mm	16mm
<b>4 M</b>	7mm	10mm	13mm	16mm
<b>6 M</b>	7mm	10mm	13mm	16mm

- Supplied with safety hooks and shortening clutches

**Chain Slings  
Grade 80 Alloy Four Leg  
Technical Specification**

E.W.L (M)	S.W.L 3.1T @ 0° - 45°	S.W.L 6.7T @ 0° - 45°	S.W.L 11.2T @ 0° - 45°	S.W.L 17T @ 0° - 45°
<b>2 M</b>	7mm	10mm	13mm	16mm
<b>3 M</b>	7mm	10mm	13mm	16mm
<b>4 M</b>	7mm	10mm	13mm	16mm
<b>6 M</b>	7mm	10mm	13mm	16mm

- Supplied with safety hooks and shortening clutches
- Can be used as 3 or 4 leg



- The three leg barrow sling is compatible with every hoist
- Particularly suited for use with both the Scaffold hoist and Gantry hoist

### Barrow Sling Technical Specification

**S.W.L**

250 kgs

### Skip Lifting Assembly Technical Specification

**S.W.L**

12 T

**C/W Spacer bars**

- For transporting skips around site using tower cranes

### Dee & Bow Shackles Technical Specification

**S.W.L**

Up to 5 T

5 T to 10 T

10 T to 17.5 T

Over 17.5 T

- Galvanised Green pin Bow Shackles
- Self colour large Dee Shackles
- Tested and certified in accordance with EN-13889
- (Grade 6)



- Lifting concrete ring sections
- In sets of two, three or four
- Up to 2T per pin

**LEWIS PINS**

- Used for lifting stone from above

**Manhole Ring Lifting pin  
Technical Specification**

**25/32/35/38mm dia. Pin**

**120/150/170/200mm Wall thickness**

**S.W.L**

**500 kgs**

**25mm**

**1 T**

**28mm**

**Buckets/Muck Skips/Tipping Skips  
Technical Specification**



**Skip Type**

**Capacity**

**Mini** 90 Litre

**Mini** 120 Litre

**Round** 250 Litre

**Round** 500 Litre

**Round** 1000 Litre

**Boat** 1000 Litre

**Fork Lift Tipping Skip** 500 Litre  
1200 Litre

**Frimeda/Deha Lifting clutches  
Technical Specification**



- For lifting pre-cast concrete segments with Frimeda/Deha fittings

**S.W.L**

**Frimeda** 0 - 2.5 T

**Frimeda** 3 - 5 T

**Deha** 2 - 2.5 T

**Deha** 4 - 5 T



**Our extensive Hire range is also available for Sale.**

In addition to our standard Hire range, we also supply various different makes and models to suit individual situations and requirements. Tailor made bespoke equipment can be designed and manufactured by Concord Lifting.

If you're after one-off site installations, permanent workshop solutions or just the reassurance that Concord's experience brings, then contact us. Not only will you receive exactly what you are after, we carry out examinations, testing and audits, giving peace of mind for safe and secure lifting solutions.



**Brick Lifts/Crane Forks, C/W safety net  
Technical Specification**

**Weekly Rate**

POA

- 2 tonne safe working load multi-purpose crane fork is an industry standard
- Combining strength, durability and versatility
- Self leveling and telescopic units available



Fork Mounting Attachment

**Block Grabs - C/W safety net  
Technical Specification**

**S.W.L**

1.8 T

1.8 T


- Model 1311 Series
- An ideal partner for the crane fork is our range of Block Grabs.

- 6 x standard Oxygen or 2 x 47kg propane
- 4 small
- 2 Small-2 Large

**Bottle Carrier**

**S.W.L**

500 kgs



### Kerb and Block Handling Technical Specification

- Continuing our range of equipment to source safe and practical solutions to every lifting operation we stock a range of kerb and stone handling equipment.

	Width (mm)	Height (mm)	Length (mm)	Weight (kgs)
<b>Kerb stone handle</b>	0 -450	200	150	150
<b>Kerb Grab</b>	50 -540	130	200	250

### Vacuum Block Grab

- Ideal for paving slabs etc
- Battery powered. C/W 240v charger

Pad	S.W.L
300 x 300mm	160 kgs

### Fork Truck Tine Brackets Technical Specification

- Provides a central lifting eye for fork lift trucks

Capacities	Internal
2/3/4 T	150 x 70mm
580mm External	270mm Internal

### Fork truck Jib Booms

- Convert a fork lift truck into a long reach crane

Range	
Capacity	
2.5 T	700 – 3700mm
5 T	700 – 3700mm



**Man-Riding Cages  
Technical Specification**

	H (mm)	W (mm)	D (mm)	Nett Weight	S.W.L
<b>2 Persons</b>	2200	1270	780	225 kgs	500 kgs
<b>4 Persons</b>	2200	1220	1220	440 kgs	1 Tonne

- Complete with 4 leg top chain assembly

**Stretcher Cages**

	H (mm)	W (mm)	D (mm)	Nett Weight	S.W.L
<b>2 Persons</b>	2000	775	259 ) 0	375 kgs	300 kgs

- Complete with 4 leg top chain assembly

**Stretchers to suit above Cage**

<b>Weekly Rate</b>
POA

**Pipe or Beam Bogie  
Technical Specification**

<b>Pipe Bogies 762kgs</b>	Up to 250mm dia
<b>Beam Bogies 762kgs</b>	340mm Internal width

- Up to 2 tonne capacity cushion rubber or pneumatic tyres



**Pallet Truck  
Technical Specification**

Model	Size
<b>Narrow</b>	520mm x 1100mm
<b>Wide</b>	680mm x 1100mm
<b>Long</b>	550mm x 2000mm

- Concord supply for hire or sale, all models of pallet truck not just the standard 2500kg capacity 690mm by 1150mm.

**All Terrain Pallet Truck**

Model	Size
<b>All Terrain</b>	1250mm internal width



- Designed for the purpose of moving brick or block packs around construction sites
- This rough terrain unit will just as easily move 1200kg pallets in warehouse or stores



- Up to 1000kg capacity rubber or pneumatic tyres

**Flat Top/ Turntable Truck  
Technical Specification**

Capacity	L(mm)	W(mm)	H(mm)
<b>500kgs</b>	1220	310	410
<b>1T</b>	1525	760	485
<b>1T</b>	2000	1000	485

- Specialised units for handling drums, cylinders and barrels also available



**Sack Trucks  
SAH 200**

Capacity	Shoe Length	Width	Shoe Width
<b>255kgs</b>	305mm	515mm	365mm



- Powered units available

**Stair  
Climber Truck**

Manual	Shoe Length	Width	Shoe Width
<b>100kgs</b>	470mm	550mm	310mm
<b>150kgs</b>	470mm	550mm	320mm
<b>300kgs</b>	227mm	640mm	480mm



- The plasterboard trolley superbly complements the Scott-Jack lifter

**Plaster-board Trolley  
Technical Specification**

S.W.L	
<b>100 kgs</b>	2 Wheel



- We have a skate for any load moving requirement.

<b>Piano Skate Technical Specification</b>			
	<b>Length (mm)</b>	<b>Width (mm)</b>	<b>Capacity</b>
<b>2 Wheel</b>	630	460	200 kgs
<b>4 Wheel</b>	630	460	200 kgs



- Ideal for heavy awkward objects
- The wheels can swivel 360° for easy manoeuvring
- Lifted by hydraulic jacks secured by ratchet straps

<b>Skoots C/W 2 x Ratchet Straps Technical Specification</b>	
<b>Capacity</b>	
1.8 T per pair	



- Any substantial piece of home or office furniture can be successfully moved with these highly popular trolleys

<b>Furniture Moving Trolley</b>			
<b>Height</b>	<b>W</b>	<b>L</b>	<b>Capacity</b>
210mm	385 mm	385 mm	1000 kgs



- Rubber cover helps grip the load
- Easy to manoeuvre

<b>Furniture Skate</b>			
<b>Height</b>	<b>W</b>	<b>L</b>	<b>Capacity</b>
150mm	305mm	610mm	40 kgs



- Essential tool when lifting and positioning heavy loads

**Roller Crowbar  
Technical specification**

**Capacity**

Pinch Bar 1.5 T

Roller Crow 5 T



**Machine Skates  
Technical Specification**



- Set of 4 including turntables, equalizers and handles

Size	L(m m)	W(m m)	H(m m)	H*(m m)	Capacity
<b>Size 1</b>	210	102	59	94	20 T
<b>Size 2</b>	271	125	95	143	30 T

H\* Includes turntable / Equaliser

**Nylon skates**



- Roller skates in set of 3, 1 steerable, 2 fixed
- Helps put awkward loads on the move
- Nylon skates only to be used on clean floors

Capacity	Overall Height(mm)
Up to 6 T	115
Up to 12 T	102
Up to 15 T	102
Up to 25 T	110

- Complete with Shock Absorbing Lanyards
- Or fixed rope Lanyard



**Safety Harness  
Technical Specification**

**Weekly Rate**  
POA

- Retractable line which locks under sudden/rapid movement



**Fall Arrest Inertia Reel**

**Length of Cable (Metres)**

2.5 M

Up to 12 M

12 M +

- 10 or 20M length
- Provides fixing point for applications where there is a danger of falling



**Temporary lifeline**

**Weekly Rate**  
POA

- Constructed from 1 Cruciform, 4 Extension arms & 12 Slottable weights
- Easy to set up  
Ideal for short term maintenance
- Working on flat roofs



**Roof man Anchor Systems**

**Weekly Rate**  
POA

**Package deal! Hire Roof Man anchor, Fall arrest Block and Safety Harness for an amazing rate!**



- Complete with Winch and Full Body harness
- Portable retrieval system offering maximum security to personnel working below ground

**Man-Riding Tripods  
Technical Specification**

**Weekly Rate**  
POA

- To suit above tripod

**Bosun's Chair**

**Weekly Rate**  
POA

**Hire and Buy Safely with Concord**

Concord will help you meet your duty of care for employee and personal safety.

We ensure all Concord products conform to the Health and Safety at Work Act.

Whether you wish to pick up goods or have them delivered, Safety in the work place or at home is part of our everyday practice. Main Points to remember: Think Safely at Heights, Think Safely when Lifting and Moving, and take every precaution in the dress code to further reduce the risk of personal injury.





- Self Contained
- Battery operated
- Lifters for lifting and fitting glass units quickly and safely
- Most models have rotation and tilt features

Concord will also maintain repair and test customers own vacuum lifters. Comes with a 12 month warranty.

- Moving glass around isn't just a question of lifting, so we keep a range of glass stillage trolleys for hire or sale
- Concord will discuss, design and build trolleys, racks or stillages to suit individual requirements

### Vacuum Handlers Technical Specification

Model	S.W.L
Woods 4 -Pad	320 kgs
Twin Woods 4 - Pad	640 kgs
MRT Cruciform Pattern	320 kgs
MRT 6 Pad	500 kgs
Glass boy one pad	500kgs
6 Pad + 2 extension pads Pannkoke 7011DS	600 kgs
Bohle 4-Pad	600 kgs
Hand Held 1/2/3 Pad	N/A
Al vac vacuum slab lifter	

### Stillage Trolley

Length	Width	Height
1600mm	800mm	1700mm


C/W 2  
Lifting eyes



**Test Weights  
Technical Specification**

**Type**

- 20kg Hand Weights
- 25kgs Hand Weights
- 500kgs Roller Weights
- Weight tray 40 x 25kgs Weights



**Load Cells/Load Indicators**

**Capacity**

- 2.5 T
- 5 T
- 10 T
- 20 T



**Testing Facilities**

Our depots all have the necessary facilities to test, re-certify & repair all major makes/models of lifting equipment featured in our Hire/Sales product range.

We also undertake 'On-site' testing of fabricated lifting equipment, including:

- Gantries
- Lift Shaft/Motor Room beams
- Overhead Cranes
- Swing Jibs
- Runway beams/Running rails

In addition our Barking and St. Neots depot specializes in the repair/testing of Vacuum Handling Equipment, with its permanent facility for vertical or horizontal 'live load' calibration & testing.

## **1. Definitions**

- a) The Contract is for the hire and the sale of goods ("Goods") detailed in the Contract, and the parties to the Contract are:
- b) The person, firm, company or other organisation hiring the Equipment and/or purchasing the Goods ("Hirer").
- c) Concord Lifting Equipment Ltd; Units 53 & 56 Wimbledon Stadium Business park, Riverside Road, London, SW17 0BE
- d) Any condition deemed invalid will not affect other conditions or the consumer's existing legal rights.

## **2. General**

- a) **Extent of Contract and Cancellation**  
The Contract is effective when Concord Lifting Equipment Ltd accepts the Hirer's order. Hires to individuals or partnerships shall not be for a period in excess of three months. In these circumstances, the Hirer must return the Equipment before the last day of the three month period.
- b) **Contract and Cancellation**  
Concord Lifting Equipment Ltd reserves the right to charge for cancellation.
- c) **Termination**  
Concord Lifting Equipment Ltd may terminate the Contract and repossess Equipment without affecting any rights to recover monies due, damages for breach of contract, where the Hirer is involved in insolvency or liquidation proceedings.
- d) **Ownership of Equipment and Goods**  
At all times, equipment hired remains the property of Concord Lifting Equipment Ltd. Ownership of Equipment purchased transfers only when full payment is received by Concord Lifting Equipment Ltd. Specifications, technical descriptions are data serve as a guide only.

## **3. Hire**

- a) **Basis of charging**  
The hire charges are for the duration of the Contract and include weekends and Public Holidays.
- b) **Transport charges**  
Delivery and collections including attempted calls are chargeable. If Equipment is not available or only partially available for collection then the Hirer will be charged for each journey on a mileage or time basis.
- c) **Deposits**  
Deposits are set by Concord Lifting Equipment Ltd at amounts reasonably required and will be offset against any monies due. If a Deposit is required it must be paid by the Hirer before the hire period. Deposit balances are refunded upon return to Concord Lifting Equipment Ltd of Equipment in good condition. Balances of deposits by cheque will be refunded by cheque or BACS within 7 business days.
- d) **Cleaning and damage repair**  
The Hirer will pay for required cleaning, re-sharpening, breakages and damage repair. The Hirer shall notify Concord Lifting Equipment Ltd immediately of all loss and damage to equipment.

e) **Loss of Equipment**

The Hirer undertakes to accept full responsibility for loss and damage to equipment from whatever cause. Concord Lifting Equipment Ltd will treat Equipment unavailable for collection from site, or un-returned after being off-hired by the hirer after reasonable notice as lost and the Hirer will pay a penalty charge for Equipment replacement and revenue loss. Hire charges accrue until full settlement is made.

#### **4. Payment**

a) **Payment Terms**

If the Hirer has a credit account then payment of any charges due under the Contract, including VAT, shall be made in full **by the end of the month following the date of the invoice**. If the Hirer does not have a credit account, then payment of any charges due under the Contract shall be made with the Hirer's order. Payment by the Hirer on time under the Contract is an essential condition of the Contract. Payment shall not be deemed to have been made until Concord Lifting Equipment Ltd has received cleared funds or cash. All business to be conducted on a Nett 30 day basis with a minimum hire period of 1 Week (7days). Over 1 week daily rate of 1/7<sup>th</sup> of weekly rate.

b) **Invoice Queries**

The Hirer should notify Concord Lifting Equipment Ltd of any queries concerning invoices in writing within 14 days of the invoice date. Concord Lifting Equipment Ltd Services will not grant an extension to credit account payment for unresolved invoice queries that have been notified after 14 days have elapsed from the invoice date.

c) **Overdue Accounts**

Should any portion of an account fall overdue then the total account will become due on demand. The Hirer will be liable for reasonable legal charges incurred by Concord Lifting Equipment Ltd in the recovery of Equipment and amounts due. In addition Concord Lifting Equipment Ltd may charge 5% per month interest in the event of the account not being paid within two calendar months of the last of the month shown as the date on our invoice and may suspend further services to the Hirer.

d) **Credit Limits**

Where Concord Lifting Equipment Ltd has granted a credit account to the Hirer, Concord Lifting Equipment Ltd may set a reasonable credit limit. Concord Lifting Equipment Ltd reserve the right to terminate or suspend the Contract if allowing it to continue would result in the Hirer exceeding his credit limit or the Hirer has already exceeded his credit limit.

#### **5. Hirer's Responsibilities**

a) **Inspection and receipt of Equipment and Goods**

The Hirer will sign to acknowledge receipt at delivery. Shortages must be agreed and noted on the delivery document. Equipment defects should be reported to Concord Lifting Equipment Ltd immediately.

b) **Delivery & collection of Equipment and Goods**

The Hirer will provide adequate delivery and collection access and be responsible for unloading and loading at delivery and collection. Equipment transported in the Hirer's own vehicle is at the Hirer's risk.

c) **Security of Equipment**

The Hirer accepts responsibility for Equipment security until its collection by or return to Concord Lifting Equipment Ltd and undertakes not to sell or relinquish possession, alter, repair or modify it in any way. The Hirer shall not sub-let or lend, sell, mortgage,

charge, pledge or part with possession of the equipment to any third party without written permission from Concord Lifting Equipment Ltd. The Hirer shall protect against distress, execution or seizure and shall indemnify Concord Lifting Equipment Ltd of all charges and expenses by failure to observe this condition.

d) **Safe use of Equipment and breakdown procedure**

The Hirer is responsible for the safe and correct operation of Equipment by competent persons not under the influence of alcohol or drugs and for its constant supervision within the range of children. The Hirer will immediately notify Concord Lifting Equipment Ltd of any Equipment breakdown or shortcoming without attempt at repair. The Hirer shall take steps to keep himself acquainted with the state and condition of equipment. If equipment is continued to be used in an unsafe state, the Hirer shall be solely responsible for all damage, loss or accidents. The Hirer will ensure any non-Concord Lifting Equipment Ltd, Equipment used in conjunction with or attached to Equipment also conforms to safety requirements. The Hirer will indemnify Concord Lifting Equipment Ltd in respect of all claims by any person for injury to persons or property caused by equipment whether arising under statute or common law.

e) **Return or collection of Equipment**

The Hirer may arrange for the return or collection of Equipment with any Concord Lifting Equipment Ltd outlet during normal business hours and when Equipment has been returned or collected Concord Lifting Equipment Ltd will issue a return note. The Hirer remains responsible for the Equipment, and in particular its security, until return or collection.

f) **Lost or stolen Equipment**

The Hirer agrees to insure Equipment on a full replacement basis against the risks of loss, theft and damage beyond economic repair and to pay to Concord Lifting Equipment Ltd any insurance claim proceeds. This liability is without prejudice to any Concord Lifting Equipment Ltd rights under the Contract.

## **6. Concord lifting Equipment' Responsibilities**

a) **Hire rates**

Concord Lifting Equipment Ltd will maintain the agreed hire rates for the duration of the Contract.

b) **Safety and operating instructions**

Concord Lifting Equipment Ltd will provide appropriate written and/or practical instruction in the safe and correct operation of Equipment.

c) **Testing and inspection of Equipment**

Concord Lifting Equipment Ltd will test all electrical Equipment before commencement of hire. Equipment will be inspected and tested in accordance with relevant statutory requirements and if Equipment needs to be recovered from the Hirer for such purposes, substitute equipment of similar specification will be supplied.

d) **Delivery and collection**

Concord Lifting Equipment Ltd will endeavor to deliver or collect Equipment at the Hirer's request during the next business day, wherever possible.

e) **Returned Goods**

Concord Lifting Equipment Ltd will arrange an appropriate credit where the Hirer returns in unused condition Goods sold for use with Equipment.

f) **Limitation of liability**

The liability of Concord Lifting Equipment Ltd for claims made by the Hirer does not extend to any unforeseeable financial loss caused by late or non-delivery of Equipment and/or Goods, unsuitability, breakdown, stoppage or lawful repossession. Subject to the above Concord Lifting Equipment Ltd will be liable for negligence or error in the performance of its obligations under the Contract.

## Concord Lifting Equipment Ltd

Specialists in the Hire, Sales and Maintenance of Lifting Equipment

Your partner for safe and secure lifting solutions.

**Concord Lifting Equipment.....**



- Specialise in the Hire, Sales & Maintenance.
- Testing services to British & European standards, both at our depots & 'on-site'.
- Design bespoke lifting equipment systems for end users to legal requirements.
- Executive Hire News Depot of 2005 Award.
- Our equipment will be safe and suitable for its intended use.
- Outstanding lifting expertise.

**Contact Details: Call 03333 660099**

**Email: [info@concordlifting.co.uk](mailto:info@concordlifting.co.uk)**

**Opening Hours: 8am-5pm Monday-Friday**

Deliveries by prior agreement on Saturdays.

### **Wandsworth**

**: Tel: 020 8946 7902**

Head Office and Accounts

Units 53 & 56, Wimbledon Stadium Business Park, Riverside Road

London, SW17 0BE

Fax: 020 8946 7001

Email: [wandsworth@concordlifting.co.uk](mailto:wandsworth@concordlifting.co.uk)

### **Barking**

**: Tel: 020 8594 7529**

Unit 4, Buzzard Creek Industrial Estate, River Road, Barking, Essex, IG11 0EL

Fax: 020 8594 8674

Email: [barking@concordlifting.co.uk](mailto:barking@concordlifting.co.uk)

### **Charlton**

**Tel: 020 8465 5835**

Units 15 & 16, Brocklebank Industrial Estate, Bugsby's Way

Charlton, London, SE7 7SX

Fax: 020 8465 5832

Email: [charlton@concordlifting.co.uk](mailto:charlton@concordlifting.co.uk)

### **St. Neots :**

**Tel: 01480 217605**

10 Foundry Way, Eaton Socon, St. Neots, Cambs, PE19 8TR

Fax: 01480 407108

Email: [stneots@concordlifting.co.uk](mailto:stneots@concordlifting.co.uk)