



"World's Most Technologically
Advanced Hearing Aid Company"



INTRODUCING

Z series™ | Halo™ BTE



PRICE LIST
w.e.f. 1st May, 2015

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
Z series i110	16 Channels & 16 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • BluWave 4.0 with Auto Experience Manager • ISO-C • Acuity Directionality with Speech id • MEMS Microphone • New microphone cover • Premium Voice iQ with Enhanced Wind Noise Management • Multiflex Tinnitus*** • 900 Sync • Stream boost • Spatial Streaming • Binaural Spatial Mapping • iQ Boost • Binaural Telephone Mode • Designed for Vibrant Lifestyle • Improved PureWave Feedback Eliminator • Spectral iQ • Live 3D Speech Mapping • Swap Fit • T² on Demand • SoundPoint • Self Learning • Voice Indicators • Rocker Switch** • Hydrashield² (Water Resistant) • In-situ Audiometry • Directionality Plus 	3,00,800
	BTE PP	20-120 dB		2,55,700
	CIC/ITC/ITE	0-90 dB		3,01,900
	CIC/ITC/ITE EXP	0-110 dB		3,19,400
	RIC	0-90 dB		2,62,300
RIC AP	0-110 dB	2,68,200		
Z series i90	12 Channels & 12 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • BluWave 4.0 with Auto Experience Manager • ISO-C • Acuity Directionality with Speech id • MEMS Microphone • New microphone cover • Advance Voice iQ with Enhanced Wind Noise Management • Multiflex Tinnitus*** • Stream boost • Spatial Streaming • Binaural Spatial Mapping • iQ Boost • Binaural Telephone Mode • Designed for Active Lifestyle • Improved PureWave Feedback Eliminator • Spectral iQ • Live Speech Mapping • Swap Fit • T² on Demand • SoundPoint • Self Learning • Voice Indicators • Rocker Switch** • Hydrashield² (Water Resistant) • In-Situ Audiometry • Directionality Plus 	2,07,600
	BTE PP	20-120 dB		1,76,400
	CIC/ITC/ITE	0-90 dB		2,08,700
	CIC/ITC/ITE EXP	0-110 dB		2,21,500
	RIC	0-90 dB		1,72,500
RIC AP	0-110 dB	1,78,400		
Z series i70	8 Channels & 8 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • BluWave 4.0 with Auto Experience Manager • ISO-C • Acuity Directionality with Speech id • MEMS Microphone • New microphone cover • Select Voice iQ with Enhanced Wind Noise Management • Multiflex Tinnitus*** • 900 Sync • Stream boost • Spatial Streaming • Binaural Spatial Mapping • iQ Boost • Binaural Telephone Mode • Designed for Social Lifestyle • Improved PureWave Feedback Eliminator • Spectral iQ • Live Speech Mapping • Swap Fit • T² on Demand • SoundPoint • Self Learning • Voice Indicators • Rocker Switch** • Hydrashield² (Water Resistant) • In-situ Audiometry • Directionality Plus 	1,18,900
	BTE PP	20-120 dB		1,01,100
	CIC/ITC/ITE	0-90 dB		1,20,100
	CIC/ITC/ITE EXP	0-110 dB		1,35,300
	RIC	0-90 dB		1,00,300
RIC AP	0-110 dB	1,06,100		
Z series i30	6 Channels & 6 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • BluWave 4.0 with Auto Experience Manager • ISO-C • Acuity Directionality with Speech id • MEMS Microphone • New microphone cover • Multiflex Tinnitus*** • 900 Sync • Stream boost • Spatial Streaming • Binaural Telephone Mode • Improved PureWave Feedback Eliminator • Spectral iQ • Swap Fit • T² on Demand • SoundPoint • Self Learning • Voice Indicators • Rocker Switch • Hydrashield² (Water Resistant) • Multiple Memories • In-situ Audiometry 	92,700
	BTE PP	20-120 dB		78,900
	CIC/ITC/ITE	0-90 dB		93,800
	CIC/ITC/ITE EXP	0-110 dB		1,07,900
	RIC	0-90 dB		74,100
RIC AP	0-110 dB	79,900		
Z series i20	4 Channels & 4 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • BluWave 4.0 with Auto Experience Manager • ISO-C • Acuity Directionality with Speech id • MEMS Microphone • New microphone cover • Multiflex Tinnitus*** • 900 Sync • Stream boost • Spatial Streaming • Binaural Telephone Mode • Improved PureWave Feedback Eliminator • Spectral iQ • Swap Fit • T² on Demand • SoundPoint • Self Learning • Voice Indicators • Rocker Switch • Hydrashield² (Water Resistant) • Multiple Memories • In-Situ Audiometry 	64,700
	BTE PP	20-120 dB		55,000
	CIC/ITC/ITE	0-90 dB		65,900
	CIC/ITC/ITE EXP	0-100 dB		74,000
	RIC	0-90 dB		54,200
RIC AP	0-110 dB	60,100		

** Model Specific

*** Available only in size 312 Micro RIC

Model	Style	Fitting Range	Features	MRP (INR) Per Unit	
Halo i110	16 Channels & 16 Bands				
	BTE ^{New}	20-110 dB	<ul style="list-style-type: none"> • BlueWave 4.0 with Auto Experience Manager • Stream Boost • Comfort Boost • Designed for Vibrant Lifestyle • TruLink Hearing Control App for iOS & Android • Acoustic Scene Analyzer with 5 levels of personalization • Premium Voice iQ • Improved PureWave Feedback Eliminator • Spectral iQ • SoundPoint • Swap Fit • Speech Mapping • Pristine Audio Streaming** • Acuity Directionality with Speech ID • ISO-C • Live Speech Mapping • Hydrashield² • In-Situ Audiometry • Binaural Spatial Mapping • Directionality Plus 	2,78,000	
	RIC	0-90 dB		2,46,500	
	RIC AP	0-110 dB		2,51,800	
Halo i90	12 Channels & 12 Bands				
	BTE ^{New}	20-110 dB	<ul style="list-style-type: none"> • BlueWave 4.0 with Auto Experience Manager • Acuity Directionality with Speech ID • ISO-C • Stream Boost • Comfort Boost • Designed for Active Lifestyle • TruLink Hearing Control App for iOS & Android • Acoustic Scene Analyzer with 3 levels of personalization • Advanced Voice iQ² • Improved PureWave Feedback Eliminator • Spectral iQ • SoundPoint • Swap Fit • Pristine Audio Streaming** • Live Speech Mapping • Hydrashield² • In-Situ Audiometry • Binaural Spatial Mapping • Directionality Plus 	1,92,700	
	RIC	0-90 dB		1,64,900	
	RIC AP	0-110 dB		1,70,200	
Halo i70	8 Channels & 8 Bands				
	BTE ^{New}	20-110 dB	<ul style="list-style-type: none"> • BlueWave 4.0 with Auto Experience Manager • Acuity Directionality with Speech ID • ISO-C • Stream Boost • Comfort Boost • Designed for Active Lifestyle • TruLink Hearing Control App for iOS & Android • Acoustic Scene Analyzer • Select Voice iQ² • Improved PureWave Feedback Eliminator • Spectral iQ • SoundPoint • Swap Fit • Pristine Audio Streaming** • Live Microphone • Live Speech Mapping • Hydrashield² • In-Situ Audiometry • Binaural Spatial Mapping • Directionality Plus 	1,28,600	
	RIC	0-90 dB		1,11,200	
	RIC AP	0-110 dB		1,16,500	

Halo i110, i90, i70 & TruLink are compatible with iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPad Air, iPad (4th Generation), iPad mini with Retina display, iPad Mini & iPod touch (5th Generation)

INTRODUCING
Our Newest Made for iPhone®
Hearing Aid

Halo™ BTE 13



Model	Style	Fitting Range	Features	MRP (INR) Per Unit
12 Channels & 12 Bands				
XiNO 90 TINNITUS	RIC	0-90 dB	<ul style="list-style-type: none"> • Multiflex Tinnitus Technology Featuring 16 Channels & 16 Bands • Sound Point Tinnitus Technology & user control • Designed for active lifestyles • High-resolution sound Imaging • PureWave Feedback Eliminator¹ • Invision Directionality² • Live Speech Mapping • Tonal & Voice Indicators • Spectral IQ • Automatic Telephone Response • T² on Demand • SoundPoint • Self Learning • Swap Fit • T² Remote • Voice IQ² • In-Situ Audiometry • Acoustic Scene Analyzer with 3 levels of personalization 	94,000
	RIC AP	0-110 dB		99,000
6 Channels & 6 Bands				
XiNO 30 TINNITUS	RIC	0-90 dB	<ul style="list-style-type: none"> • Multiflex Tinnitus Technology Featuring 16 Channels & 16 Bands • Sound Point Tinnitus Technology & user control • Designed for Calm Lifestyle • Voice IQ² • T² Remote • PureWave Feedback Eliminator² • Invision Directionality¹ (Optional) • Automatic Telephone Response • Tonal & Voice Indicators • T² on Demand • In-Situ Audiometry 	38,800
	RIC AP	0-110 dB		43,800
4 Channels & 4 Bands				
XiNO 20 TINNITUS	RIC	0-90 dB	<ul style="list-style-type: none"> • Multiflex Tinnitus Technology Featuring 16 Channels & 16 Bands • Sound Point Tinnitus Technology & user control • Designed for Basic Lifestyle • Feedback Canceller • Invision Directionality² (Optional) • Tonal & Voice Indicators • Automatic Telephone Response 	33,700
	RIC AP	0-110 dB		38,700

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
8 Channels & 12 Bands				
XiNO 110 CLASSIC	RIC	0-90 dB	<ul style="list-style-type: none"> • Analog VC • Voice Indicators • Feedback Canceller • Directionality • Expanded Data Log • Feature Validation • Noise Control • 7 Acoustic Signatures : Quiet, Speech, Speech-in-Noise, Machine Noise, Noise, Wind, Directional • In-Situ Audiometry 	85,000
	RIC AP	0-110 dB		90,000
8 Channels & 12 Bands				
XiNO 90 CLASSIC	RIC	0-90 dB	<ul style="list-style-type: none"> • Analog VC • Tone Indicators • Feedback Canceller • Directionality • Expanded Data Log • Feature Validation • Noise Control • 5 Acoustic Signatures : Quiet, Speech, Machine Noise, Noise, Wind, Directional • In-Situ Audiometry 	75,000
	RIC AP	0-110 dB		80,000
8 Channels & 10 Bands				
XiNO 70 CLASSIC	RIC	0-90 dB	<ul style="list-style-type: none"> • Analog VC • Tone Indicators • Feedback Canceller • Directionality • Expanded Data Log • Feature Validation • Noise Control • 4 Acoustic Signatures : Quiet, Noise, Wind, Directional • In-Situ Audiometry 	60,000
	RIC AP	0-110 dB		65,000
4 Channels & 8 Bands				
XiNO 30 CLASSIC	RIC	0-90 dB	<ul style="list-style-type: none"> • Analog VC • Tone Indicators • Feedback Canceller • Directionality • Data Log • Feature Validation • Noise Control • 4 Acoustic Signatures : Quiet, Noise, Wind, Directional 	37,000
	RIC AP	0-110 dB		42,000
2 Channels & 8 Bands				
XiNO 20 CLASSIC	RIC	0-90 dB	<ul style="list-style-type: none"> • Analog VC • Feedback Canceller • Directionality • Tone Indicators • Noise Control • 3 Acoustic Signatures: Quiet, Noise, Directional 	26,000
	RIC AP	0-110 dB		31,000

SMALL AND COMFORTABLE



XiNO
TINNITUS

Relief from
RINGING
in your ears is here

Prices are subject to change without any prior notice.



Model	Style	Fitting Range	Features	MRP (INR) Per Unit
16 Channels & 16 Bands				
XiNO i110 WIRELESS	RIC	0-90 dB	<ul style="list-style-type: none"> • ISO Compression • Premium Voice iQ² • Designed for vibrant lifestyles • Optimal high-resolution sound imaging • Binaural Spatial Mapping • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ • Swap Fit • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • T² on Demand • Sound Point • Self Learning • Acoustic Scene Analyzer with 5 levels of personalization • In-Situ Audiometry 	2,38,500
	RIC AP	0-110 dB		2,43,800
12 Channels & 12 Bands				
XiNO i90 WIRELESS	RIC	0-90 dB	<ul style="list-style-type: none"> • ISO Compression • Advanced Voice iQ² • Designed for active lifestyles • High-resolution sound imaging • Binaural Spatial Mapping • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ • Sound Point • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • Self Learning • T² on Demand • Swap Fit • Acoustic Scene Analyzer with 3 levels of personalization • In-Situ Audiometry 	1,56,900
	RIC AP	0-110 dB		1,62,200
8 Channels & 8 Bands				
XiNO i70 WIRELESS	RIC	0-90dB	<ul style="list-style-type: none"> • ISO Compression • Select Voice iQ² • Designed for social lifestyles • Precise sound imaging • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ • Sound Point • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • T² on Demand • Swap Fit • Self Learning • Acoustic Scene Analyzer • In-Situ Audiometry 	91,200
	RIC AP	0-110 dB		96,500
6 Channels & 6 Bands				
XiNO i30 WIRELESS	RIC	0-90 dB	<ul style="list-style-type: none"> • ISO Compression • Designed for Calm Lifestyle • Sound Imaging • Voice iQ² • PureWave Feedback Eliminator³ • Synchronized User Controls • Compatible with all SurfLink Accessories • Advanced Memories • T² on Demand • InVision Directionality³ • Automatic Telephone Solutions • Hydrashield² • Spectral iQ • Live Speech Mapping • In-Situ Audiometry 	58,300
	RIC AP	0-110 dB		63,300
4 Channels & 4 Bands				
XiNO i20 WIRELESS	RIC	0-90 dB	<ul style="list-style-type: none"> • ISO Compression • Designed for Basic Lifestyle • Feedback Canceller • Synchronized User Controls • Compatible with all SurfLink Accessories • Advanced Memories • InVision Directionality³ • Automatic Telephone Solutions • Hydrashield² • Spectral iQ • Voice iQ² 	39,800
	RIC AP	0-110 dB		44,800

WIRELESS 312 MICRO RIC

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
16 Channels & 16 Bands				
XiNO 110	RIC	0-90 dB	<ul style="list-style-type: none"> • Designed for Vibrant Lifestyle • Optimum High-resolution sound Imaging • PureWave Feedback Eliminator • Acoustic Scene Analyzer with 5 levels of personalization • Premium Voice iQ² • Spectral iQ • Self Learning • T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories • T² Remote • Voice Indicators • Hydrashield² • Swap Fit • SoundPoint • In-Situ Audiometry 	2,07,800
	RIC AP	0-110 dB		2,13,100
12 Channels & 12 Bands				
XiNO 90	RIC	0-90 dB	<ul style="list-style-type: none"> • Designed for Active Lifestyle • High-resolution sound Imaging • PureWave Feedback Eliminator • Acoustic Scene Analyzer with 3 levels of personalization • Advanced Voice iQ² • Spectral iQ • Self Learning • T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories • Voice Indicators • Hydrashield² • T² Remote • Swap Fit • SoundPoint • In-Situ Audiometry 	1,36,700
	RIC AP	0-110 dB		1,42,000
8 Channels & 8 Bands				
XiNO 70	RIC	0-90 dB	<ul style="list-style-type: none"> • Designed for Social Lifestyle • Precise Sound Imaging • PureWave Feedback Eliminator • Acoustic Scene Analyzer • Select Voice iQ² • Spectral iQ • Self Learning • T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories • Voice Indicators • Hydrashield² • SoundPoint • Swap Fit • T² Remote • In-Situ Audiometry 	79,500
	RIC AP	0-110 dB		84,800
6 Channels & 6 Bands				
XiNO 30	RIC	0-90 dB	<ul style="list-style-type: none"> • PureWave Feedback Eliminator • Environmental Detection • Spectral iQ • Live Real Ear Measurement • Swap Fit • Invision Directionality • Multiple Memories • Voice Indicators • Automatic Telephone Response • Sweep Technology • Hydrashield² • Self Learning • Select Noise Adaptation • T² on Demand • T² Remote • In-Situ Audiometry 	45,600
	RIC AP	0-110 dB		50,900
4 Channels & 4 Bands				
XiNO 20	RIC	0-90 dB	<ul style="list-style-type: none"> • PureWave Feedback Eliminator • Invision Directionality • Multiple Memories • Voice Indicators • Automatic Telephone Response • Sweep Technology • Hydrashield² • Self Learning • Spectral iQ • Swap Fit • Select Noise Adaptation • T² Remote 	30,700
	RIC AP	0-110 dB		36,000

NON WIRELESS 10 MINI RIC



Model	Style	Fitting Range	Features	MRP (INR) Per Unit
3 series i110	16 Channels & 16 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • ISO Compression • Premium Voice iQ² • Designed for vibrant lifestyles • Optimal high-resolution sound imaging • Binaural Spatial Mapping² • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Automatic Telephone Response • Hydrashield² • Rocker Switch • Swap Fit • T² on Demand • Sound Point • Self Learning • Voice Indicators • Acoustic Scene Analyzer with 5 levels of personalization • In-Situ Audiometry 	2,73,500
	BTE PP	20-120 dB		2,32,500
	CIC/ITC/ITE	0-90 dB		2,74,500
	CIC/ITC/ITE ExP	0-110 dB		2,90,400
	RIC	0-90 dB		2,38,500
RIC AP	0-110 dB	2,43,800		
3 series i90	12 Channels & 12 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • ISO Compression • Advanced Voice iQ² • Designed for active lifestyles • High-resolution sound imaging • Binaural Spatial Mapping² • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • Rocker Switch • Swap Fit • T² on Demand • Sound Point • Self Learning • Acoustic Scene Analyzer with 3 levels of personalization • In-Situ Audiometry 	1,88,700
	BTE PP	20-120 dB		1,60,400
	CIC/ITC/ITE	0-90 dB		1,89,700
	CIC/ITC/ITE ExP	0-110 dB		2,01,400
	RIC	0-90 dB		1,56,900
RIC AP	0-110 dB	1,62,200		
3 series i70	8 Channels & 8 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • ISO Compression • Select Voice iQ² • Designed for social lifestyles • Precise sound imaging • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • Rocker Switch • Swap Fit • T² on Demand • Sound Point • Self Learning • Acoustic Scene Analyzer • In-Situ Audiometry 	1,08,100
	BTE PP	20-120 dB		91,900
	CIC/ITC/ITE	0-90 dB		1,09,200
	CIC/ITC/ITE ExP	0-110 dB		1,23,000
	RIC	0-90 dB		91,200
RIC AP	0-110 dB	96,500		
3 series i30	6 Channels & 6 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • 100% Wireless • ISO Compression • Synchronized User Adjustments • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Environmental Detection • InVision Directionality³ (Optional) • Multiple Memories • Voice Indicators • Automatic Telephone Response • T² on Demand • Spectral iQ • Hydrashield² • Rocker Switch • Select Voice iQ² • In-Situ Audiometry 	84,300
	BTE PP	20-120 dB		71,700
	CIC/ITC/ITE	0-90 dB		85,300
	CIC/ITC/ITE ExP	0-110 dB		98,100
	RIC	0-90 dB		67,300
RIC AP	0-110 dB	72,600		
3 series i20	4 Channels & 4 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • 100% Wireless • ISO Compression • Synchronized User Adjustments • Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator³ • Environmental Detection • InVision Directionality³ (Optional) • Multiple Memories • Voice Indicators • Automatic Telephone Response • Spectral iQ • Hydrashield² • Select Voice iQ² • Rocker Switch 	58,800
	BTE PP	20-120 dB		50,000
	CIC/ITC/ITE	0-90 dB		59,900
	CIC/ITC/ITE ExP	0-100 dB		67,300
	RIC	0-90 dB		49,300
RIC AP	0-110 dB	54,600		

100% WIRELESS WITH IRIS TECHNOLOGY.
BTEs are available in 13 & 312 battery size.

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
3 series 110	16 Channels & 16 Bands			
	IIC	0-110 dB	<ul style="list-style-type: none"> • ISO Compression • Premium Voice iQ² • Designed for vibrant lifestyles • Optimal high-resolution sound imaging • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Hydrashield² • Rocker Switch • T² on Demand • Sound Point • Self Learning • Swap Fit • T² Remote • Acoustic Scene Analyzer with 5 levels of personalization • In-Situ Audiometry 	2,79,800
	BTE	20-110 dB		2,61,800
	BTE PP	20-120 dB		2,22,500
	CIC/ITC/ITE	0-90 dB		2,62,900
	CIC/ITC/ITE ExP	0-110 dB		2,78,800
RIC	0-90 dB	2,27,900		
RIC AP	0-110 dB	2,33,200		
3 series 90	12 Channels & 12 Bands			
	IIC	0-110 dB	<ul style="list-style-type: none"> • ISO Compression • Advanced Voice iQ² • Designed for active lifestyles • Sound imaging • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Voice Indicators • Automatic Telephone Response • Sound Point • Hydrashield² • T² Remote • Rocker Switch • T² on Demand • Self Learning • Swap Fit • Acoustic Scene Analyzer with 3 levels of personalization • In-Situ Audiometry 	2,06,700
	BTE	20-110 dB		1,80,200
	BTE PP	20-120 dB		1,53,200
	CIC/ITC/ITE	0-90 dB		1,81,300
	CIC/ITC/ITE ExP	0-110 dB		1,92,900
RIC	0-90 dB	1,49,500		
RIC AP	0-110 dB	1,54,800		
3 series 70	8 Channels & 8 Bands			
	IIC	0-110 dB	<ul style="list-style-type: none"> • ISO Compression • Select Voice iQ² • Designed for social lifestyles • Precise Sound Imaging • PureWave Feedback Eliminator³ • Spectral iQ • InVision Directionality³ (Optional) • Live Speech Mapping • Voice indicators • Automatic Telephone Response • Sound Point • Hydrashield² • T² Remote • Rocker Switch • T² on Demand • Self Learning • Swap Fit • Acoustic Scene Analyzer • In-Situ Audiometry 	1,21,900
	BTE	20-110 dB		1,03,900
	BTE PP	20-120 dB		88,300
	CIC/ITC/ITE	0-90 dB		1,04,900
	CIC/ITC/ITE ExP	0-110 dB		1,18,700
RIC	0-90 dB	86,900		
RIC AP	0-110 dB	92,200		
3 series 30	6 Channels & 6 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • ISO Compression • PureWave Feedback Eliminator³ • Environmental Detection • InVision Directionality³ (Optional) • Multiple Memories • Voice Indicators • Automatic Telephone Response • Spectral iQ • Hydrashield² • Rocker Switch • T² Remote • T² on Demand • In-Situ Audiometry 	69,400
	BTE PP	20-120 dB		59,000
	CIC/ITC/ITE	0-90 dB		70,500
	CIC/ITC/ITE ExP	0-110 dB		83,200
	RIC	0-90 dB		50,400
RIC AP	0-100 dB	55,700		
3 series 20	4 Channels & 4 Bands			
	BTE	20-110 dB	<ul style="list-style-type: none"> • ISO Compression • PureWave Feedback Eliminator³ • Environmental Detection • InVision Directionality³ (Optional) • Multiple Memories • Voice Indicators • Automatic Telephone Response • Spectral iQ • Hydrashield² • Rocker Switch • T² Remote 	39,200
	BTE PP	20-120 dB		38,100
	CIC/ITC/ITE	0-90 dB		41,900
	CIC/ITC/ITE ExP	0-100 dB		49,300
	RIC	0-90 dB		34,500
RIC AP	0-100 dB	38,700		
SurfLink Accessories				
Model	Features			MRP (INR) Per Unit
SurfLink Mobile 2	SurfLink Mobile 2: is a one-of-a-kind cell phone solution, breakthrough assistive listening device, handy hearing aid remote & intuitive TV & music streaming device all rolled into one.			31,500
SurfLink Media	SurfLink Media: Allows patient to wirelessly connect to virtually any media device with no pairing or body-worn device required.			27,500
SurfLink Remote	SurfLink Remote: Provides patients with a way to adjust their hearing instruments discreetly & easily.			8,900

NON WIRELESS TECHNOLOGY.
BTEs are available in 312 battery size.

3 series

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
16 Channels & 16 Bands				
Wi i110	CIC/ITC/ITE	0-90 dB	<ul style="list-style-type: none"> 100% Wireless • Designed for Vibrant Lifestyle Optimal High-resolution sound imaging • Premium Binaural Spatial mapping • Synchronized User Adjustments • Binaural Telephone mode • Premium Voice IQ² • T² on Demand Invision Directionality • PureWave Feedback Eliminator • Live Real Ear Measurement • Live Speech mapping • Self Check SoundPoint • Swap Fit • Self Learning • Spectral IQ Compatible with all SurfLink Accessories • iQ Boost Acoustic Scene Analyzer with 5 levels of personalization In-Situ Audiometry 	2,30,000
	CIC/ITC/ITE ExP [#]	0-110 dB		2,45,900
	RIC	0-90 dB		2,25,800
	RIC AP	0-110 dB		2,27,900
12 Channels & 12 Bands				
Wi i90	CIC/ITC/ITE	0-90 dB	<ul style="list-style-type: none"> 100% Wireless • Designed for Active Lifestyle • High-resolution sound imaging • Advanced Binaural Spatial mapping Synchronized User Adjustments • Binaural Telephone mode • Advanced Voice IQ² • T² on Demand • Invision Directionality PureWave Feedback Eliminator • Live Real Ear Measurement Live Speech mapping • Swap Fit • Self Learning Sound Point • Spectral IQ • Compatible with all SurfLink Accessories • iQ Boost • Acoustic Scene Analyzer with 3 levels of personalization • In-Situ Audiometry 	1,53,700
	CIC/ITC/ITE ExP [#]	0-110 dB		1,79,100
	RIC	0-90 dB		1,49,500
	RIC AP	0-110 dB		1,52,600
8 Channels & 8 Bands				
Wi i70	CIC/ITC/ITE	0-90 dB	<ul style="list-style-type: none"> 100% Wireless • Designed for Social Lifestyle • Precise Sound imaging • Synchronized User Adjustments • Binaural Telephone mode • Select Voice IQ² • T² on Demand • Invision Directionality PureWave Feedback Eliminator • Live Real Ear Measurement Live Speech mapping • Swap Fit • Self Learning • Sound Point • Spectral IQ • Compatible with all SurfLink Accessories • iQ Boost • Acoustic Scene Analyzer In-Situ Audiometry 	99,600
	CIC/ITC/ITE ExP [#]	0-110 dB		1,21,000
	RIC	0-90 dB		89,200
	RIC AP	0-110 dB		94,500
6 Channels & 6 Bands				
ignite i30	CIC/ITC/ITE	0-90 dB	<ul style="list-style-type: none"> 100% Wireless • Synchronized User Adjustments • iQ Boost Binaural Telephone Mode • Compatible with all SurfLink Accessories • PureWave Feedback Eliminator • Environmental Detection • Live Real Ear Measurement • Directionality Multiple Memories • Voice Indicators • Spectral IQ • Swap Fit Automatic Telephone Response • Sweep Technology • T² on Demand Hydrashield² (Water Resistant) • Voice IQ² • Self Learning In-Situ Audiometry 	73,700
	CIC/ITC/ITE ExP [#]	0-110dB		84,800
	RIC	0-90 dB		58,800
	RIC AP	0-110 dB		64,100
4 Channels & 4 Bands				
ignite i20	CIC/ITC/ITE	0-90 dB	<ul style="list-style-type: none"> 100% Wireless • Synchronized User Adjustments • iQ Boost • Binaural Telephone Mode • Spectral IQ Compatible with all SurfLink Accessories • PureWave Feedback Eliminator • Environmental Detection • Live Real Ear Measurement • Directionality • Multiple Memories • Voice Indicators Automatic Telephone Response • Sweep Technology • Self Learning Hydrashield² (Water Resistant) • Voice IQ² • Swap Fit 	51,400
	CIC/ITC/ITE ExP [#]	0-100 dB		58,800
	RIC	0-90 dB		39,500
	RIC AP	0-100 dB		45,500

* Only available with 60 dB gain.

[#] Wireless ITE/CIC ExP available with 60 dB gain.

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
16 Channels & 16 Bands				
Xseries 110	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Vibrant Lifestyle • Optimal High-resolution sound Imaging • PureWave Feedback Eliminator • Acoustic Scene Analyzer with 5 levels of personalization • Voice IQ² • Spectral IQ SoundPoint • Self Learning • T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories • Invisible Option • Voice Indicators Hydrashield² • Swap Fit • In-Situ Audiometry 	2,56,500
	BTE	20-110 dB		2,38,500
	BTE PP	20-120 dB		1,59,000
	CIC/ITC/ITE	0-90 dB		2,39,600
	CIC/ITC/ITE ExP	0-110 dB		2,55,500
	RIC	0-90 dB		2,07,800
	RIC AP	0-110 dB		2,13,100
12 Channels & 12 Bands				
Xseries 90	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Active Lifestyle • High-resolution sound Imaging PureWave Feedback Eliminator • Acoustic Scene Analyzer with 3 levels of personalization • Voice IQ² • Spectral IQ • SoundPoint Self Learning • T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories Voice Indicators • Hydrashield² • Swap Fit • In-Situ Audiometry 	1,88,700
	BTE	20-110 dB		1,63,200
	BTE PP	20-120 dB		1,16,600
	CIC/ITC/ITE	0-90 dB		1,64,300
	CIC/ITC/ITE ExP	0-110 dB		1,74,900
	RIC	0-90 dB		1,36,700
	RIC AP	0-110 dB		1,42,000
8 Channels & 8 Bands				
Xseries 70	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Social Lifestyle • Precise Sound Imaging PureWave Feedback Eliminator • Acoustic Scene Analyzer Voice IQ² • Spectral IQ • SoundPoint • Self Learning T² on Demand • Sweep Technology • Live Real Ear Measurement • Automatic Telephone Response • Live Speech Mapping • Invision Directionality • Self check • Multiple memories Voice Indicators • Hydrashield² • Swap Fit • In-Situ Audiometry 	1,11,300
	BTE	20-110 dB		93,300
	BTE PP	20-120 dB		77,200
	CIC/ITC/ITE	0-90 dB		94,300
	CIC/ITC/ITE ExP	0-110 dB		1,07,100
	RIC	0-90 dB		79,500
	RIC AP	0-110 dB		84,800
6 Channels & 6 Bands				
ignite 30	BTE	20-110 dB	<ul style="list-style-type: none"> PureWave Feedback Eliminator • Environmental Detection Spectral IQ • Live Real Ear Measurement • T² Remote Invision Directionality • Multiple Memories • Voice Indicators Automatic Telephone Response • Sweep Technology Hydrashield² • Self Learning • Voice IQ² • Swap Fit T² on Demand • In-Situ Audiometry 	60,400
	BTE PP	20-120 dB		47,700
	CIC/ITC/ITE	0-90 dB		61,500
	CIC/ITC/ITE ExP	0-110 dB		74,200
	RIC	0-90 dB		45,600
	RIC AP	0-110 dB		50,900
4 Channels & 4 Bands				
ignite 20	BTE	20-110 dB	<ul style="list-style-type: none"> PureWave Feedback Eliminator • Invision Directionality • Multiple Memories • Voice Indicators • Automatic Telephone Response Sweep Technology • Hydrashield² • Self Learning Spectral IQ • Swap Fit • Voice IQ² 	39,200
	BTE PP	20-120 dB		37,100
	CIC/ITC/ITE	0-90 dB		40,300
	CIC/ITC/ITE ExP [*]	0-100 dB		47,700
	RIC	0-90 dB		30,700
	RIC AP	0-100 dB		36,000

* Only available with 60 dB gain.



Model	Style	Fitting Range	Features	MRP (INR) Per Unit
16 Channels & 16 Bands				
S series iQ11	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Vibrant Lifestyle • Optimal high resolution sound Premium Voice IQ² • Invision Directionality • Acoustic Scene Analyzer 5 levels of personalization • PureWave Feedback Eliminator Audioscapes includes Machine Noise, Speech in noise, Wind & Quiet • Live Real Ear Measurement • Live Speech mapping Self check • Voice indicators • Automatic Telephone Response T² Remote • Invisible Options • SoundPoint • T² on Demand Appointment follow up indicator • Multiple Memories Swap Fit • Self Learning • In-Situ Audiometry 	2,33,200
	BTE	20-110 dB		2,19,200
	CIC/ITC/ITE	0-90 dB		2,20,300
	CIC/ITC/ITE ExP	0-110 dB		2,33,000
	RIC	0-90 dB		1,91,200
	RIC AP	0-110 dB		1,96,500
12 Channels & 12 Bands				
S series iQ9	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Active Lifestyle • High-resolution sound imaging Advanced Voice IQ² • Invision Directionality Acoustic Scene Analyzer with 3 levels of personalization PureWave Feedback Eliminator • Live real Ear Measurement Live Speech mapping • Voice indicators • Automatic Telephone Response • T² Remote • T² on Demand • Invisible Options • Multiple Memories • Sound Point • Swap Fit • Self Learning • In-Situ Audiometry 	1,71,500
	BTE	20-110 dB		1,49,200
	CIC/ITC/ITE	0-90 dB		1,50,300
	CIC/ITC/ITE ExP	0-110 dB		1,60,900
	RIC	0-90 dB		1,24,900
	RIC AP	0-110 dB		1,30,200
8 Channels & 8 Bands				
S series iQ7	IIC	0-110 dB	<ul style="list-style-type: none"> Designed for Social Lifestyle • Precise Sound imaging • Select Voice IQ² • Invision Directionality • Acoustic Scene Analyzer PureWave Feedback Eliminator • Live Real Ear Measurement Live Speech mapping • Voice indicators • Automatic Telephone Response • T² Remote • T² on Demand • Invisible Options • Multiple Memories • Sound Point • Swap Fit • Self Learning • In-Situ Audiometry 	1,00,500
	BTE	20-110 dB		86,700
	CIC/ITC/ITE	0-90 dB		87,800
	CIC/ITC/ITE ExP	0-110 dB		97,300
	RIC	0-90 dB		71,900
	RIC AP	0-110 dB		77,200
6 Channels & 6 Bands				
S series 5	BTE	20-110 dB	<ul style="list-style-type: none"> Designed for Calm Lifestyle • Sound imaging • PureWave Feedback Eliminator • Sweep Technology • Live Real Ear Measurement • Live Speech mapping • Automatic Telephone Response • T² on Demand • T² Remote • Voice indicators Multiple Memories • In-Situ Audiometry 	55,000
	Mini BTE	0-100 dB		55,000
	CIC/ITC/ITE	0-90 dB		56,100
	CIC/ITC/ITE ExP	0-110 dB		64,600
	RIC	0-90 dB		40,200
RIC AP	0-110 dB	45,500		

Model	Style	Fitting Range	Features	MRP (INR) Per Unit
4 Channels & 4 Bands				
S series 3	BTE	20-110 dB	<ul style="list-style-type: none"> Automatic Telephone Response • Sweep Technology Feedback Cancellor • Environmental Adaption • Dynamic Directionality • 4 Memories Standard • Induction Coil • Volume Control • Voice Indicator 	30,700
	Mini BTE	0-100 dB		30,700
	CIC/ITC/ITE	0-90 dB		29,700
	CIC/ITC/ITE ExP	0-110 dB		35,600
	RIC	0-90 dB		27,600
	RIC AP	0-110 dB		32,800
2 Channels & 8 Bands				
S series 2	BTE	0-95 dB	<ul style="list-style-type: none"> Feedback Cancellor • Environmental Adaption • 4 Memories Standard • Induction Coil • Volume Control 	20,100
	Mini BTE	0-90 dB		18,600
	BTE P	20-110 dB		23,300
	CIC/ITC/ITE	0-90 dB		21,100
	CIC/ITC/ITE ExP	0-100 dB		24,900
Earplugs				
Products		Material Used		MRP (INR) Per Unit
Ear Protection Device	I-Pod, MP3 Earplugs		UV Material	2,400
	Musicians Earplugs		Biopore Material	2,400
	High Frequency Noise Filter		Biopore Material	2,400
	Floatable Swimmer Earplugs		Biopore Material	1,500
	Solid Earplugs		Biopore Material	580
	Sleeping Earplugs		Biopore Material	580
	BTE Hard Mold		UV Material	380
	BTE Soft Mold		Biopore Material	580
Repair Charges				
S.No	Hearing Aids		Repair Charges	Warranty
1.	Dp7, B13 DX, K2000 Series, Aries, Aries-Pro, SM Vega, Dp8, PsP, PxP, Destiny 200, E2, E3		1650	6 Months
2.	Ignite 20/20, Ignite 30/30, Destiny 800 PP, Destiny 400, S5, 3 Series 20 /20, 3 Series 30/30, Xino 20, Xino 30, Z Series i20, Z Series i30.		3150	6 Months
3.	Destiny 800, S7, S7iQ, X-70, Wi-i70, 3 Series- 70/70, Destiny 1200, Destiny 1200 (Power Plus), S9, S9iQ, Wi-i90, 3 Series- 90/90, Destiny 1600, S11, S11iQ, X-110, Wi-i110, 3 Series 110/i110, Xino i70/70, Xino i90/90, Xino i110/100, Xino Tinnitus, Halo i70, Halo i90, Halo i110, Z Series i70, Z Series i90, Z Series i110.		5850	6 Months
EXTRA RECIEVER FOR RIC			MRP (Rs.)	
40/50 (dB)			6800	
60/71 (dB)			7800	

**THE BEST
JUST GOT
SMALLER**

INTRODUCING
SOUNDLens 2

The World's First IIC
is now even Smaller



Repair issues related to Battery Door, Pulling Thread, Mic Cover Replacement, Volume Control, Ear Hook, Wax guard & General Servicing (Clean & Check) @ Rs 500/- Inclusive of Taxes.

Repair Conditions:-

- Above charges are applicable per aid.
- Physical damage or damage due to battery leakage will not be covered under repair warranty.
- Taxes as per actual.

Return for Credit Policy*	Upgrade Policy*	Exchange Policy*
<ol style="list-style-type: none"> Hearing aids returned within 90 days from the invoice date, full credit note of the invoice amount will be issued, However restocking charges of Rs 2500/- shall be charged. Hearing aids returned after 90 days but within 180 days from date of invoice date, credit note will be issued subject to deduction of 25% of the original invoice price. Hearing aids returned after 180 days, no credit note will be issued. 	<ol style="list-style-type: none"> Applicable only on hearing aids returned within 90 days from the date of invoice. Applicable only from Starkey Mid level technology onwards. Only the differential amount between the existing aid & the upgrade aid shall be charged. The warranty period shall remain same as that of the previous hearing aids. 	<ol style="list-style-type: none"> In case of exchange, a trade in value equal to 50% of the billed price (in case of Starkey hearing aid) or 25% of the billed price or current MRP whichever is lower (in case of Non Starkey Hearing Aid) will be deducted from the MRP of new product.

RESELLING CHARGES

IIC	: Rs 5,000 Each
Wireless Custom	: Rs 5,000 Each
Others	: Rs 2,500 Each

TECHNOLOGY LEVELS (For upgrade & exchange policy)

Entry	: Dp7, B13DX, K2000 Series, Aries, Aries-Pro, SM VEGA
Economy	: Dp8, PsP, PXP, DDS, IDW, IDP, Destiny 200, E2, E3, Ignite-20/i20, 3Series 20/i20, Xino20, Z Series i20
Mid	: Destiny 400/800, S5,S7,S7 iQ, Ignite-30/i30, X-70, Wi-i70, 3 Series 30/i30, 3 Series-70/i70, Xino i70/70 & Xino 30, Halo i70, Z Series i70, Z Series i30.
High	: Destiny 1200, Destiny 1200(Power Plus), S9, S9iQ, X-90, Wi-i90, 3 Series-90/i90, Xino i90/90 & Xino Tinnitus, Halo i90, Z Series i90.
Premium	: Destiny 1600, S11, S11iQ, X-110, Wi-i110, 3 Series-110/i110, Xino i110/110, Halo i110, Z Series i110

Conditions Apply

- * Starkey reserves the right to limit or refuse to accept the return of certain product at any time without assigning any reasons.
- * Products must not be damaged or mishandled at the time of receipt.
- * There will be no exchange or up gradation in case of special orders or supplies made on special terms/schemes.
- * For exact calculation under exchange & upgrade policies, please contact Starkey representative.
- * Exchange & upgrade policies are applicable only to next higher technology level subject to company policy from time to time.
- * If the patient feels uncomfortable with new exchanged or upgraded product within a month, then the patient can return the new product & can take back old product. Difference whatsoever charged will be credited back by the company to the dealer. Company will dismantle or scrap the hearing aids received under exchange/upgrade schemes after one month.



SURFLINK[®]

MOBILE 2



The one device that does it all

The Industry's most unique and versatile cell phone device. SurfLink Mobile2 combined with our wireless hearing aids. SurfLink Mobile 2 is everything your patients need to help with phone conversation plus enjoy TV & music, listen to presenters & live life without limitations!!

SurfLink Mobile is compatible with Starkey's Z Series, 3 Series, Wi Series, Xino™ and Ignite™

IIC: Invisible in the Canal. **BTE:** Behind-the Ear. **CIC:** Completely-in-the-Canal. **ITC:** In-The-Canal. **ITE:** In-the-Ear. **RIC:** Receiver-in-the-canal. **AP:** Absolute Power (with occluded molds only). **Exp:** Extreme Power. **PP:** Power Plus. **P:** Power

** All Starkey Hearing Instrument carries two years world wide warranty.

Prices are subject to change without prior notice.

WIRELESS + TINNITUS SOLUTION TOGETHER

The latest in hearing aid technology



Z series

Starkey Laboratories India Pvt. Ltd.
C-2, Sector-7, Noida-201301
Ph. : +91-120-4081000-29
Fax : +91-120-4081030
www.starkeyindia.com
marketing_support_india@starkey.com



Starkey Laboratories Inc
6700, Washington Avenue South
Eden Prairie MN 55344-3476
800.328.8602
www.starkey.com