



## Company profile:

- ➔ Safe Vision Technology Co., Ltd is professional in developing, manufacturing, selling of consumptive video monitor products such as IP Camera, Analog Camera, CCTV Kit, NVR, DVR etc.
- ➔ Our factory is located in Shenzhen, China, manufacturing facilities cover an excess of 6500 square meters, staffed by over 500 dedicated manufacturing and engineering professionals.
- ➔ The company has passed ISO9001:2000 quality management system and all the products have passed standard certifications of FCC, CE, ROHS etc.
- ➔ 90% of Safe Vision products are exported to over 20 nations and districts all over the world. We also set offices in the US and Russia. Our products are widely accepted and well recognized by our customers by the high cost performance, high quality, fine service and humanized appearance designs.
- ➔ Since foundation, Safe Vision has paid great attention to cooperation, win-win and share relationships with customers, partners and employees.



• Production Building



• Office Building



• Company Reception



• Office part



• Show Room



• Production Team



• Business Team



• SMT Line



• DIP Line



• PCBA Testing



• Aging Room



• Assembly Line



• Semi-finished products testing



• Overall testing



• Stock

**Your Safety is our duty!**

## Network Camera

www.safe-dvr.com

ZK-IPH-WA4310



ONVIF

- Standard 3.0mega pixel IP camera
- 1/3" HD Sensor
- 20fps@3.0M(2048\*1536) 25/30fps @1080P resolution
- Built-in 6mm(3.6/8mm optional)
- IR-Cut,Day/night switch
- 3 streaming for network
- Support POE function
- IP66 20-30m IR visual distance

ZK-IPH-BA4311F



ONVIF

- Standard 3.0mega pixel IP camera
- High-performance TI DaVinci series DSP
- H.264 video compression and JPEG image capture
- 20fps@3.0M(2048\*1536) 25/30fps @1080P resolution
- Dual encoding streams supported
- Support ICR true Day/Night
- Support C/CS Auto Iris lens
- Support Alarm I/O, RS485 interface
- Max 32GB Hot-swappable SD card for local storage
- Support DC12V/AC24V dual power supply, POE
- Built-in Web server, NVR, CMS

ZK-IPH-DA4211



ONVIF

- Standard 2.0mega pixel IP camera
- 1/3" HD Sensor
- 1080P 30fps
- Built-in 3.6mm(6/8mm optional)
- 3 streaming for network
- Support POE function

ZK-IPH-DB4211



ONVIF

- 2.0mega pixel IP camera
- 1/3" HD Sensor
- 1080P 30fps
- Built-in 6mm(6/8/12mm optional)
- WDR,D&N
- Support POE function

ZK-IPH-WB4210



ONVIF

- Standard 2.0mega pixel IP camera
- 1/3" HD Sensor
- 1080P 30fps
- Built-in 6mm(3.6/8mm optional)
- IR-Cut,Day/night switch
- 3 streaming for network
- IP66 10-20m IR visual distance
- Support POE function

ZK-IPH-WC4211



ONVIF

- Standard 2.0mega pixel IP camera
- 1/3" HD Sensor
- 1080P 30fps
- Built-in 2.8-12mm
- IR-Cut,Day/night switch
- 2 streaming for network
- IP66 20-30m IR visual distance
- Support POE function

## Analog Camera

www.safe-dvr.com

Model:D21PC2-B

Model:W02PC3-B



- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High performance CMOS sensor
- 24pcs  $\phi$ 5 IR led, IR distance 20M
- Auto AGC & White Balance
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP65 protection level, good heat Dissipation design



- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High performance CMOS sensor
- 24pcs  $\phi$ 5 IR led, IR distance 20M
- Auto AGC & White Balance
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP66 protection level, good heat Dissipation design

Model:W01PC3-W

Model:W02PC3-W



- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High performance CMOS sensor
- 24pcs  $\phi$ 5 IR led, IR distance 20M
- Auto AGC & White Balance
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP66 protection level, good heat Dissipation design



- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High performance CMOS sensor
- 24pcs  $\phi$ 5 IR led, IR distance 20M
- Auto AGC & White Balance
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP66 protection level, good heat Dissipation design

Model:W21PS4

Model:W32PS4-F



- 1/3 Sony 700TVL
- Built-in 6mm(4/8/12mm optional)
- High performance Sony CCD
- 42pcs  $\phi$ 5 IR led, IR distance 50M
- Pure white metal case, beauty design
- Support BLC, OSD optional
- Support AGC, automatic backlight
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP66 protection level, good heat Dissipation design



- 1/3 Sony 700TVL
- Built-in 6mm(4/8/12mm optional)
- High performance Sony CCD
- 4pcs high power lattice LED, IR distance 80M
- Pure white metal case, beauty design
- Support BLC, OSD optional
- Support AGC, automatic backlight
- Effective Pixels: PAL:960H\*582V, NTSC:976H\*494V
- IP66 protection level, good heat Dissipation design

## HD-SDI DVR

Model:9104D-4S



- 4CH HD-SDI video input
- 1CH SDI playback
- 4CH audio inputs/1ch audio output
- 4ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 4 SATA(each can up to 2TB)
- Standard 2U case

Model:9108D-8S



- 8CH HD-SDI video input
- 2CH SDI playback
- 8CH audio inputs/1ch audio output
- 8ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- Standard 2U case

Model:9116D-16S



- 16CH HD-SDI video input
- 4CH SDI playback
- 16CH audio inputs/1ch audio output
- 16ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- Standard 2U case

Model:7109D-9X



- 1CH HD-SDI+8CH D1 video input
- 1CH SDI, 8CH D1 playback
- 9CH audio inputs/1ch audio output
- 8ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:6104D-4I



- 4CH HD-SDI video input
- 1CH SDI playback
- 4CH audio inputs/1ch audio output
- 4ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:6104D-4H



- 4CH HD-SDI video input
- 1CH SDI playback
- 4CH audio inputs/1ch audio output
- 4ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

## NVR

Model:6208N-Z



- 8CH 1080P video inputs
- 1CH 1080 playback
- 4CH audio inputs/1ch audio output
- 4ch alarm inputs/1ch alarm output
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:6208N-L



- 8CH 1080P IPC inputs
- 1CH 1080 playback
- 4CH audio inputs/1ch audio output
- 4ch alarm inputs/1ch alarm output
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:8316N-H



- 16CH 1080P video inputs
- 1CH 1080 playback
- 8CH audio inputs/1ch audio output
- 4ch alarm inputs/1ch alarm output
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:8316N-I



- 16CH 1080P IPC inputs
- 1CH 1080 playback
- 8CH audio inputs/1ch audio output
- 4ch alarm inputs/1ch alarm output
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:9124N-S



- 24CH 1080P video input
- 1CH 1080 playback
- 16CH audio inputs/1ch audio output
- 16ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- Standard 2U case

Model:9124N-S



- 24CH 1080P IPC inputs
- 1CH 1080 playback
- 16CH audio inputs/1ch audio output
- 16ch alarm inputs/4ch alarm outputs
- Support TV,VGA,HDMI video output simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- Standard 2U case

## DVR Kit


Model: 4 Camera Kit



### DVR

- 4CH D1 realtime recording
- 4CH D1 playback
- 1CH audio input/1CH audio output
- Support TV,VGA simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 1 SATA(each can up to 2TB)

Support mobile



1. 1\*4CH digital video recorder
2. 1\*remote control, 1\*mouse
3. 1\*user manual
4. 1\*5A power supply
5. 4\*CMOS 600TVL camera
6. 4\*18M cable
7. 1/5 splitter power line



### CAMERA

- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High quality real color rendition
- 24pcs LED, IR distance 10M
- PAL/NTSC optional
- Auto Electronic Shutter
- Low illumination, BLC
- High S/N Ratio
- Auto-switch ICR Infrared filter, good performance in day and night


Model:8 Camera Kit



### DVR

- 2CH D1+6CIF realtime recording
- 8CH HD1 playback
- 8CH audio inputs/1CH audio output
- 4CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI(optional) simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Support mobile



1. 1\*8CH digital video recorder
2. 1\*remote control, 1\*mouse
3. 1\*user manual
4. 1\*5A power supply  
1\*4A power supply
5. 8\*CMOS 600TVL camera
6. 8\*18M cable
7. 1/8 splitter power line



### CAMERA

- 1/3 CMOS 600TVL
- Built-in 3.6mm
- High quality real color rendition
- 36pcs LED, IR distance 20-30M
- PAL/NTSC optional
- Auto Electronic Shutter
- Low illumination, BLC
- High S/N Ratio
- Auto-switch ICR Infrared filter, good performance in day and night

## DVR

www.safe-dvr.com

Model:6204H-4A

Model:6204F-4Z

**960H**



- 4CH 960H realtime recording
- 4CH 960H playback
- 4CH audio inputs/1CH audio output
- 4CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)
- NVR,HVR,DVR all in one



- 4CH D1 realtime recording
- 4CH D1 playback
- 4CH audio inputs/1CH audio output
- 4CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)
- NVR,HVR,DVR all in one

Model:8316-16I

Model:7116A-16X



- 16CH D1 realtime recording
- 1CH D1 playback
- 16CH audio inputs/1CH audio output
- 4CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)
- NVR,HVR,DVR all in one



- 16CH D1 realtime recording
- 16CH D1 playback
- 16CH audio inputs/1CH audio output
- 8CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 3 SATA, 1 e-SATA(each can up to 2TB)
- Standard 1.5U case
- NVR,HVR,DVR all in one

Model:9116H-16S

Model:9116A-16S

**960H**



- 16CH 960H realtime recording
- 8CH 960H playback
- 16CH audio inputs/1CH audio output
- 16CH alarm inputs/4CH alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- Standard 2U case
- NVR,HVR,DVR all in one



- 16CH D1 realtime recording
- 16CH D1 playback
- 16CH audio inputs/1CH audio output
- 16CH alarm inputs/4CH alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 8 SATA(each can up to 2TB)
- NVR,HVR,DVR all in one

## DVR (D1+CIF)

www.safe-dvr.com

Model:5004S-1T

Model:5008S-1T



- 4CH D1 realtime recording
- 1CH D1 playback
- 1CH audio input/1CH audio output
- Support TV,VGA simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 1 SATA(each can up to 2TB)



- 2CH D1+6CIF realtime recording
- 8CH HD1 playback
- 1CH audio input/1CH audio output
- Support TV,VGA simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 1 SATA(each can up to 2TB)

Model:7124F-4X

Model:7132F-4X



- 24CH CIF realtime recording
- 8CH CIF playback
- 4CH audio inputs/1CH audio output
- 8CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry,Symbian and Android OS
- Support 2 SATA(each can up to 2TB)



- 32CH CIF realtime recording
- 8CH CIF playback
- 4CH audio inputs/1CH audio output
- 4CH alarm inputs/1CH alarm output
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry, Symbian and Android OS
- Support 2 SATA(each can up to 2TB)

Model:9124F-16S

Model:9132F-16S



- 8CH D1+16CH CIF Recording
- 8CH D1+8CH CIF Playback
- 16CH audio inputs/1CH audio output
- 16CH alarm inputs/4CH alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry,Symbian and Android OS
- Support 8 SATA(each can up to 2TB)



- 8CH D1+24CH CIF Recording
- 8CH D1+8CH CIF Playback
- 16CH audio inputs/1CH audio output
- 16CH alarm inputs/4CH alarm outputs
- Support TV,VGA,HDMI simultaneously
- Support plug and play
- Support iPhone, WindowsMobile, Blackberry,Symbian and Android OS
- Support 8 SATA(each can up to 2TB)