



BEST HARDWARE

DINGZ

Mobile:86-18331061138

Com

QU

Name:	Specifications:	Length:(MM)
Roofing nail	8BWG*2"	50.8
	8BWG*2.5"	63.5
	8BWG*3"	76.2
	9BWG*1.5"	38
	9BWG*2"	50.8
	9BWG*2.5"	63.5
	9BWG*3"	76.2
	10BWG*1.75"	44.5
	10BWG*2"	50.8
	10BWG*2.5"	63.5
	11BWG*1.5"	38
	11BWG*1.75"	44.5
	11BWG*2"	50.8
	11BWG*2.5"	63.5
	12BWG*1.5"	38
	12BWG*1.75"	44.5
	12BWG*2"	50.8
	13BWG*1.5"	38
	13BWG*1.75"	44.5
	13BWG*2"	50.8
Common nail	17BWG*0.75"	20
	16BWG*1"	25
	15BWG*1.25"	20-30
	14BWG*1.5"	40
	13BWG*2"	50
	12BWG*2.5"	65
	10BWG*3"	80
	8BWG*4"	100
	6BWG*5"	120
	5BWG*6"	150
4BWG*7"	180	
Concrete nail	2*20	2*25
	2.5*25	2.5*30
	3*30	3*40
	3*60	3*70
	3*90	3*100
	4.2*75	4.2*100

Galvanized iron wire	<ol style="list-style-type: none"> 1. Material: High quality low carbon steel 2. Classification: Galvanized coil wire, 3. Electro galvanized wire: Zinc coating 4. Hot dipped galvanized wire: 40-90g 5. The standard wire gauge: BWG 6-26 6. Tensile strength: 35kg/square millimeter 7. Packing: Plastic film inside and heavy plastic outside 8. Usually we can load 25-27Tons into a 40' container
PVC coated iron wire	<ol style="list-style-type: none"> 1. PVC coating: the lowest coating 0.4mm 2. Tensile strength: 30-55kg/square millimeter 3. Color: green, blue, yellow, orange, gray 4. Package: Wrapped plastic film and heavy plastic outside
Black annealed iron wire	<ol style="list-style-type: none"> 1. The standard size: BWG 5-39. 2. Tensile strength 30-55kg/square millimeter 3. Package: 1-500kg/coil, lined with PVC
Hexagonal wire mesh	<ol style="list-style-type: none"> 1. Material: Weaved by galvanized wire 2. Weaving types: positive twist, negative twist 3. First weaved then galvanized or first galvanized then weaved 4. Hot dipped galvanized hexagonal mesh 5. Electro galvanized hexagonal mesh 6. PVC coated hexagonal mesh. 7. Stainless steel hexagonal mesh.
Welded wire mesh	<ol style="list-style-type: none"> 1. material: low carbon iron wire 2. Process: galvanized after weaving 3. specification : hot-dipped galvanized 4. Features: flat surface, uniform mesh 5. Application: widely used in industry 6. Package: lined with water proof paper
Square wire mesh	<ol style="list-style-type: none"> 1. Material: galvanized iron wire. 2. Weave: plain weave and wave weave 3. Features: structure of precision, uniform 4. Application: widely used in industry
Chain link fence	<ol style="list-style-type: none"> 1. Material: low carbon steel wire, Al-Mn 2. Weaving and characteristics: weaving 3. Application: used in protection of roads
Barbed wire fence	<ol style="list-style-type: none"> 1. Material: galvanized steel wire, PVC 2. Variety: single barbed wire, double twisted 3. Application: mainly serves in protection 4. Package: in rolls.
Razor barbed wire	Put buckles of stainless steel or zinc

The spiral intersecting barbed net p
BTO-10 BTO-12 BTO-18 BTO-22 BTO

Window screen

Material:low carbon iron wire,aluminum
Classification:galvanized window screen
Features:good toughness,light and tight
Application:heat preservation,Uvprotection
Package:5 rolls or 10 rolls per woven

ZHOU BEST HARDWARE CO.,CHINA.

Dingningdian,DingZhou,HeBei,China

Tel:86-312-5903672

Fax:86-312-5903662

Contact:Tyne Liu

Email: tyne-best@hotmail.com

QUOTATION SHEET

Diameter:(MM)	Packing:	
4.19	1.Woodenbox,blue inside	
4.19	7bs*6carton	
4.19	2.Woodenbox loosing packing	
3.73	20kg	Twisted sha
3.73	25kg	Galvanized
3.73	30kg	Diamond p
3.73	35kg	Umbrella h
3.37	48kg	
3.37	3.Case,blue inside	
3.37	7bs*8carton	
3.02	4.Case(loose)	
3.02	20kg	
3.02	25kg	
3.02	5.Matting(loose)	
2.74	25kg	
2.74	50kg	
2.74		
2.38		
2.38		
2.38		
1.45	Like roofing nail.	
1.65	Or as your request.	Plished
1.85		Iron wire
2.2		Flat head o
2.5-2.8		Diamond p
2.8-3.0		Straight an
3.4		Anti-corrosi
4		
5		
5.5		
6		
2*30	1.20-25kg/carton	White galva
2.5*40	2.20-25kg/wooden case	Diamond p
3*50	3.100pcs/box,any box/carton	Twisted or s
3*80	4.75pcs/box,any box/carton	
	5.400g/box,50box/carton	
4.2*125	6.500g/box,40box/carton	

eel.

.Cut wire,U-type wire,Flat wire,Twist wire.

g:10-30g/square meter.

/square meter.

5.

eter.

sian cloth or woven plastic bag outside,and we can make the weight for ea

1*20'FCL.

mm.

ilimeter.

y and so on.

then nylon woven bag or hessian cloth.

ilimeter.

C strips and wrapped with plastic bag or hessian cloth.

e,stainless steel wire,copper wire ect.For the size we can produce in accord

ive twist,positive and negative twist.

st galvanized then weaved.

nesh.

1.

nd galvanized before weaving.

d welded wire mesh,electro galvanized welded wire mesh,pvc coated weld

,firm welding,pleasing in form prevent,aging and corrosion,quick and easy

,agriculture,nurturing,construction,transportation and mining,etc.

er then plastic film outside.

ve

orm mesh,with good corrosion resistance and durable characteristics.

and construction,select the sad,filtration of gases and liquids,it can also b

G

ng and welding.

ad,railway,airport,residential district,port and dok,garden,feeding,farming

coated wire,stainless steel wire.


wisted barbed wire.

:ting of grassland,railway,highway etc.

coated steel sheet between two pieces of blade-gill wire net to make strer

presents interesting state after unrolling with beautiful feature and practicality-30 BTO-60 BTO-65

aluminum-magnesium alloy wire, polyethylene, fiberglass.
stainless steel, aluminum-magnesium alloy window screen, nylon window screen, fiberglass, stainless steel, anti aging and rust, easy to clean, environmentally friendly
protection, anti-mosquito
packaging: bag or carton, lined with pvc plastic film.



ink or plain shank.

oint
ead

r checkered
oint
d smooth shank
ive

vanized, black galvanized, color galvanized
oint
straight shank

ch roll as customer's requirement.

dance with customer requirements.

ed wire mesh.
installation.

e used for mechanical attachment security and protection.

etc.

ngth nore.

ality.

glass window screen.